




23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com

SELF-BALLASTED COMPACT FLUORESCENT


Self Ballasted - Spiral



Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Replaces	Initial Lum.	Lum/Watt	Life	MOL in./mm	Color Temp.	CRI
SP13/27K*†	00031	13	Med Screw (E26)	1	24	Std. 60W Incan.	900	69.2	10000	4.10/104	2700	82
SP13/35K*	00032	13	Med Screw (E26)	1	24	Std. 60W Incan.	800	61.5	10000	4.10/104	3500	82
SP13/41K†	00033	13	Med Screw (E26)	1	24	Std. 60W Incan.	782	60.2	10000	4.10/104	4100	82
SP15/65K	49321	15	Med Screw (E26)	1	24	Std. 60W Incan.	950	63.3	10000	5.0/127	6500	82
SP19/27K*†	00034	19	Med Screw (E26)	1	24	Std. 75W Incan.	1200	63.2	10000	4.73/120	2700	82
SP19/35K*	00035	19	Med Screw (E26)	1	24	Std. 75W Incan.	1200	63.2	10000	4.73/120	3500	82
SP19/41K†	00036	19	Med Screw (E26)	1	24	Std. 75W Incan.	1140	60	10000	4.73/120	4100	82
SP23/27K*†	49325	23	Med Screw (E26)	1	24	Std. 100W Incan.	1600	70	10000	4.96/126	2700	82
SP23/35K*	81171	23	Med Screw (E26)	1	24	Std. 100W Incan.	1536	66.8	10000	4.96/126	3500	82
SP23/41K	49326	23	Med Screw (E26)	1	24	Std. 100W Incan.	1472	64	10000	4.96/126	4100	82
SP27/27K*	05412	27	Med Screw (E26)	1	24	Std. 110W Incan.	1750	65	10000	5.47/139	2700	80
SP27/35K	05413	27	Med Screw (E26)	1	24	Std. 110W Incan.	1700	63	10000	5.47/139	3500	80
SP27/41K	05414	27	Med Screw (E26)	1	24	Std. 110W Incan.	1700	63	10000	5.47/139	4100	80
SP27/50K	05415	27	Med Screw (E26)	1	24	Std. 110W Incan.	1650	61	10000	5.47/139	5000	80
SP32/27K*	05416	32	Med Screw (E26)	1	24	Std. 130W Incan.	2100	66	10000	5.63/143	2700	80
SP32/35K	05417	32	Med Screw (E26)	1	24	Std. 130W Incan.	2100	66	10000	5.63/143	3500	80
SP32/41K	05418	32	Med Screw (E26)	1	24	Std. 130W Incan.	2050	64	10000	5.63/143	4100	80
SP32/50K	05419	32	Med Screw (E26)	1	24	Std. 130W Incan.	2000	63	10000	5.63/143	5000	80
SP42/27K*	05420	42	Med Screw (E26)	1	24	Std. 150W Incan.	2800	67	10000	7.13/181	2700	80
SP42/35K	05421	42	Med Screw (E26)	1	24	Std. 150W Incan.	2750	65	10000	7.13/181	3500	80
SP42/41K	05422	42	Med Screw (E26)	1	24	Std. 150W Incan.	2750	65	10000	7.13/181	4100	80
SP42/50K	05423	42	Med Screw (E26)	1	24	Std. 150W Incan.	2650	63	10000	7.13/181	5000	80

* Energy Star rated for superior energy efficiency
† TCLP Compliant

Self Ballasted - High Watt Spiral



Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Replaces	Initial Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
SP85/41/MED	81183	85	Med Screw (E26)	1	1	400W Incan.	5500	64.7	8000	11	4100	82
SP85/50/MED†	81181	85	Med Screw (E26)	1	1	400W Incan.	5500	64.7	8000	11	5000	82
SP105/41/MED†	81184	105	Med Screw (E26)	1	1	500W Incan.	6900	65.7	8000	11.5	4100	82
SP105/41/MOG	81185	105	Mog Screw (E39)	1	1	500W Incan.	6900	65.7	8000	12	4100	82
SP105/41/MOG-277V	04412	105	Mog Screw (E39)	1	1	500W Incan.	6900	65.7	8000	12	4100	82
SP105/50/MED	81180	105	Med Screw (E26)	1	1	500W Incan.	6900	65.7	8000	11.5	5000	82

† TCLP Compliant



EiKO Certified Green lamps are environmentally friendly in their manufacturing, construction, operation and/or disposal.

Look for lamps that are ENERGY STAR® rated, TCLP compliant, feature long life or high lumens per watt to provide quality light output with a minimum environmental footprint.




23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679


www.eiko.com
eiko@eiko.com

SELF-BALLASTED COMPACT FLUORESCENT


Self Ballasted - GU24 Base Spiral

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Replaces	Initial Lum.	Lum/Watt	Life	MOL mm.	Color Temp.	CRI
	SP13/27-GU24	05255	13	GU24	1	1	60W Incan.	800	61.5	10000	82	2700	82
	SP18/27-GU24	05256	18	GU24	1	1	75W Incan.	1100	61.1	10000	90	2700	82
	SP26/27-GU24	05258	26	GU24	1	1	100W Incan.	1600	62	10000	95	2700	82


Self Ballasted PAR Fluorescent

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Replaces	Initial Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	PAR38/20/27K	05531	20	Med Screw (E26)	1	1	75W Incan.	960	48	10,000			2700

Self Ballasted - R30 & R40 Reflector Flood


	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Replaces	Initial Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	R30/15/27K	49365	15	Med Screw (E26)	1	1	60W Incan.	750	50	8000	5.25	2700	82
	R30/15/41K	49366	15	Med Screw (E26)	1	1	60W Incan.	750	50	8000	5.25	4100	82
	R30/15/65K	49367	15	Med Screw (E26)	1	1	60W Incan.	750	50	8000	5.25	6500	82
	R30/20/27K	49368	20	Med Screw (E26)	1	1	75W Incan.	950	47.5	8000	6.25	2700	82
	R30/20/41K	49369	20	Med Screw (E26)	1	1	75W Incan.	950	47.5	8000	6.25	4100	82
	R30/20/65K	49370	20	Med Screw (E26)	1	1	75W Incan.	950	47.5	8000	6.25	6500	82
	R40/23/27K	49371	23	Med Screw (E26)	1	1	100W Incan.	1150	50	8000	6.5	2700	82
	R40/23/41K	49372	23	Med Screw (E26)	1	1	100W Incan.	1150	50	8000	6.5	4100	82
R40/23/65K	49373	23	Med Screw (E26)	1	1	100W Incan.	1150	50	8000	6.5	6500	82	

Self Ballasted - A11 & A15


	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Replaces	Initial Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	A11/30K	05581	11	Med Screw (E26)	1	1	40W Incan.	460	41.8	8000	5.75	3000	82
	A15/27K	49356	15	Med Screw (E26)	1	1	60W Incan.	825	55	8000	5.75	2700	82
	A15/30K	05564	15	Med Screw (E26)	1	1	60W Incan.	825	55	8000	5.75	3000	82

SPIRAL • DUOTUBE® • QUADTUBE® • TRIPLETUBE • FML COMPACT FLUORESCENT

4-Pin Spiral

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Replaces	Initial Lum.	Lum/Watt	Life	MOL mm.	Color Temp.	CRI
	SP13/27-4P	05251	13	GX24q-1	1	1	60W Incan.	860	66.2	10000	95	2700	82
	SP18/27-4P	05250	18	GX24q-2	1	1	75W Incan.	1100	61.1	10000	112	2700	82
	SP26/27-4P	05252	26	GX24q-3	1	1	100W Incan.	1600	61.5	10000	120	2700	82

Adapters for Duo and Quad Tubes

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.
	A13	15552			Med Screw (E26)	1




23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679


www.eiko.com
eiko@eiko.com


SPIRAL • DUOTUBE® • QUADTUBE® • TRIPLETUBE • FML COMPACT FLUORESCENT

T4 DuoTube® - 2 Pin Base - Beveled End  TCLP Compliant



Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Initial Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
DT5/27	15554	5	G23	1	50	250	210	50	10000	4.2	2700	82
DT5/35	49204	5	G23	1	50	250	210	50	10000	4.2	3500	82
DT5/41	49205	5	G23	1	50	250	210	50	10000	4.2	4100	82
DT5/50	49206	5	G23	1	50	250	210	50	10000	4.2	5000	82
DT5/65	49207	5	G23	1	50	250	210	50	10000	4.2	6500	82
DT7/27	15556	7	G23	1	50	400	330	57.1	10000	5.3	2700	82
DT7/35	49208	7	G23	1	50	400	330	57.1	10000	5.3	3500	82
DT7/41	49209	7	G23	1	50	400	330	57.1	10000	5.3	4100	82
DT7/50	49210	7	G23	1	50	400	330	57.1	10000	5.3	5000	82
DT7/65	49211	7	G23	1	50	400	330	57.1	10000	5.3	6500	82
DT9/27	15558	9	G23	1	50	600	500	66.7	10000	6.6	2700	82
DT9/35	49212	9	G23	1	50	600	500	66.7	10000	6.6	3500	82
DT9/41	49213	9	G23	1	50	600	500	66.7	10000	6.6	4100	82
DT9/50	49214	9	G23	1	50	600	500	66.7	10000	6.6	5000	82
DT9/65	49215	9	G23	1	50	600	500	66.7	10000	6.6	6500	82
DT13/27	15560	13	GX23	1	50	825	710	63.5	10000	7.3	2700	82
DT13/30	49216	13	GX23	1	50	825	710	63.5	10000	7.3	3000	82
DT13/35	15575	13	GX23	1	50	825	710	63.5	10000	7.3	3500	82
DT13/41	49217	13	GX23	1	50	825	710	63.5	10000	7.3	4100	82
DT13/50	49218	13	GX23	1	50	825	710	63.5	10000	7.3	5000	82
DT13/65	49219	13	GX23	1	50	825	710	63.5	10000	7.3	6500	82

T5 DuoTube® - 2G11 Base - 4 Pin - use w/ Rapid Start  TCLP Compliant



Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Initial Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
DT18/30/RS	49283	18	2G11	1	50	1250	1130	62.8	20000	9.0	3000	82
DT18/35/RS	49284	18	2G11	1	50	1250	1130	62.8	20000	9.0	3500	82
DT18/41/RS	49285	18	2G11	1	50	1250	1130	62.8	20000	9.0	4100	82
DT18/50/RS	49286	18	2G11	1	50	1250	1130	62.8	20000	9.0	5000	82
DT24/30/RS	49288	24	2G11	1	50	1800	1620	67.5	20000	12.9	3000	82
DT24/35/RS	49289	24	2G11	1	50	1800	1620	67.5	20000	12.9	3500	82
DT24/41/RS	49290	24	2G11	1	50	1800	1620	67.5	20000	12.9	4100	82
DT24/50/RS	49291	24	2G11	1	50	1800	1620	67.5	20000	12.9	5000	82
DT24/65/RS	49292	24	2G11	1	50	1800	1620	67.5	20000	12.9	6500	82
DT36/30/RS	49293	36	2G11	1	50	2900	2610	72.5	20000	16.6	3000	82
DT36/35/RS	49294	36	2G11	1	50	2900	2610	72.5	20000	16.6	3500	82
DT36/41/RS	49295	36	2G11	1	50	2900	2610	72.5	20000	16.6	4100	82
DT36/50/RS	49296	36	2G11	1	50	2900	2610	72.5	20000	16.6	5000	82
DT36/65/RS	49297	36	2G11	1	50	2900	2610	72.5	20000	16.6	6500	82
DT40/30/RS	49298	40	2G11	1	50	3300	2970	74.3	20000	22.5	3000	82
DT40/35/RS	49299	40	2G11	1	50	3300	2970	74.3	20000	22.5	3500	82
DT40/41/RS	49300	40	2G11	1	50	3300	2970	74.3	20000	22.5	4100	82
DT40/50/RS	49301	40	2G11	1	50	3300	2970	74.3	20000	22.5	5000	82
DT40/65/RS	49302	40	2G11	1	50	3300	2970	74.3	20000	22.5	6500	82
DT50/30/RS	49303	50	2G11	1	50	4300	3870	77.4	14000	22.5	3000	82
DT50/35/RS	49304	50	2G11	1	50	4300	3870	77.4	14000	22.5	3500	82
DT50/41/RS	49305	50	2G11	1	50	4300	3870	77.4	14000	22.5	4100	82
DT50/50/RS	49306	50	2G11	1	50	4300	3870	77.4	14000	22.5	5000	82
DT50/65/RS	49307	50	2G11	1	50	4300	3870	77.4	14000	22.5	6500	82
DT55/30/RS	49308	55	2G11	1	50	4800	4320	78.5	14000	21.1	3000	82
DT55/35/RS	49309	55	2G11	1	50	4800	4320	78.5	14000	21.1	3500	82
DT55/41/RS	49310	55	2G11	1	50	4800	4320	78.5	14000	21.1	4100	82
DT55/50/RS	49311	55	2G11	1	50	4800	4320	78.5	14000	21.1	5000	82
DT55/65/RS	49312	55	2G11	1	50	4800	4320	78.5	14000	21.1	6500	82

Lamps are dimmable to 10%





23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com


SPIRAL • DUOTUBE® • QUADTUBE® • TRIPLETUBE • FML COMPACT FLUORESCENT

T4 TripleTube - 4 Pin Base - Amalgam - Beveled End  TCLP Compliant


	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Initial Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
		TT18/27	49259	18	GX24q-2	1	50	1200	1020	56.7	10000	4.8	2700
TT18/30		49260	18	GX24q-2	1	50	1200	1020	56.7	10000	4.8	3000	82
TT18/35		49261	18	GX24q-2	1	50	1200	1020	56.7	10000	4.8	3500	82
TT18/41		49262	18	GX24q-2	1	50	1200	1020	56.7	10000	4.8	4100	82
TT18/50		49263	18	GX24q-2	1	50	1200	1020	56.7	10000	4.8	5000	82
TT18/65		49264	18	GX24q-2	1	50	1200	1020	56.7	10000	4.8	6500	82
TT26/27		49265	26	GX24q-3	1	50	1800	1530	58.8	10000	5.2	2700	82
TT26/30		49266	26	GX24q-3	1	50	1800	1530	58.8	10000	5.2	3000	82
TT26/35		49267	26	GX24q-3	1	50	1800	1530	58.8	10000	5.2	3500	82
TT26/41		49268	26	GX24q-3	1	50	1800	1530	58.8	10000	5.2	4100	82
TT26/50		49269	26	GX24q-3	1	50	1800	1530	58.8	10000	5.2	5000	82
TT26/65		49270	26	GX24q-3	1	50	1800	1530	58.8	10000	5.2	6500	82
TT32/27		49271	32	GX24q-3	1	50	2200	1870	58.4	10000	5.8	2700	82
TT32/30		49272	32	GX24q-3	1	50	2200	1870	58.4	10000	5.8	3000	82
TT32/35		49273	32	GX24q-3	1	50	2200	1870	58.4	10000	5.8	3500	82
TT32/41		49274	32	GX24q-3	1	50	2200	1870	58.4	10000	5.8	4100	82
TT32/50		49275	32	GX24q-3	1	50	2200	1870	58.4	10000	5.8	5000	82
TT32/65		49276	32	GX24q-3	1	50	2200	1870	58.4	10000	5.8	6500	82
TT42/27		49277	42	GX24q-4	1	50	3200	2720	64.8	10000	6.4	2700	82
TT42/30		49278	42	GX24q-4	1	50	3200	2720	64.8	10000	6.4	3000	82
TT42/35		49279	42	GX24q-4	1	50	3200	2720	64.8	10000	6.4	3500	82
TT42/41		49280	42	GX24q-4	1	50	3200	2720	64.8	10000	6.4	4100	82
TT42/50		49281	42	GX24q-4	1	50	3200	2720	64.8	10000	6.4	5000	82
TT42/65		49282	42	GX24q-4	1	50	3200	2720	64.8	10000	6.4	6500	82

Lamps are dimmable to 10%

T4 QuadTube® - FML Series  TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Initial Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
		FML18/65	05148	18	GX10q-4	1	50	1400	1080	60	10000	5.1	6500
FML27/27		49313	27	GX10q-4	1	50	1400	1260	46.7	10000	5.7	2700	82
FML27/41		49314	27	GX10q-4	1	50	1400	1260	46.7	10000	5.7	4100	82
FML27/65		49315	27	GX10q-4	1	50	1400	1260	46.7	10000	5.7	6500	82
FML36/27		49316	36	GX10q-6	1	50	2600	2340	46.7	10000	10.0	2700	82
FML36/41		49317	36	GX10q-6	1	50	2600	2340	46.7	10000	10.0	4100	82
FML36/65		49318	36	GX10q-6	1	50	2600	2340	46.7	10000	10.0	6500	82

T4 QuadTube® - 2 Pin Base - Beveled End  TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Initial Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
		QT9/27	15562	9	G23-2	1	50	550	470	52.2	10000	4.3	2700
QT9/30		49220	9	G23-2	1	50	550	470	52.2	10000	4.3	3000	82
QT9/35		49221	9	G23-2	1	50	550	470	52.2	10000	4.3	3500	82
QT13/27		15564	13	GX23-2	1	50	810	685	52.7	10000	4.6	2700	82
QT13/30		49222	13	GX23-2	1	50	810	685	52.7	10000	4.6	3000	82
QT13/35		15576	13	GX23-2	1	50	810	685	52.7	10000	4.6	3500	82
QT13/41		49084	13	GX23-2	1	50	810	685	52.7	10000	4.6	4100	82
QT13/50		49223	13	GX23-2	1	50	810	685	52.7	10000	4.6	5000	82
QT13/65		49224	13	GX23-2	1	50	810	685	52.7	10000	4.6	6500	82
QT13/G24D1/27		49225	13	G24d-1	1	50	900	765	58.8	10000	5.5	2700	82
QT13/G24D1/30		49226	13	G24d-1	1	50	900	765	58.8	10000	5.5	3000	82
QT13/G24D1/35		49227	13	G24d-1	1	50	900	765	58.8	10000	5.5	3500	82
QT13/G24D1/41		49228	13	G24d-1	1	50	900	765	58.8	10000	5.5	4100	82
QT13/G24D1/50		49229	13	G24d-1	1	50	900	765	58.8	10000	5.5	5000	82
QT13/G24D1/65		49230	13	G24d-1	1	50	900	765	58.8	10000	5.5	6500	82
QT18/27		15566	18	G24d-2	1	50	1150	980	54.4	10000	5.9	2700	82
QT18/30		49231	18	G24d-2	1	50	1150	980	54.4	10000	5.9	3000	82
QT18/35		49232	18	G24d-2	1	50	1150	980	54.4	10000	5.9	3500	82

Continued on next page ►►



23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com

SPIRAL • DUOTUBE® • QUADTUBE® • TRIPLETUBE • FML COMPACT FLUORESCENT

T4 QuadTube - 2 Pin Base - Beveled End (Continued) TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Initial Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	QT18/41	49233	18	G24d-2	1	50	1150	980	54.4	10000	5.9	4100	82
	QT18/50	49234	18	G24d-2	1	50	1150	980	54.4	10000	5.9	5000	82
	QT18/65	49235	18	G24d-2	1	50	1150	980	54.4	10000	5.9	6500	82
	QT26/27	15568	26	G24d-3	1	50	1710	1460	56.2	10000	6.7	2700	82
	QT26/30	49236	26	G24d-3	1	50	1710	1460	56.2	10000	6.7	3000	82
	QT26/35	49237	26	G24d-3	1	50	1710	1460	56.2	10000	6.7	3500	82
	QT26/41	49238	26	G24d-3	1	50	1710	1460	56.2	10000	6.7	4100	82
	QT26/50	49239	26	G24d-3	1	50	1710	1460	56.2	10000	6.7	5000	82
	QT26/65	49240	26	G24d-3	1	50	1710	1460	56.2	10000	6.7	6500	82

T4 QuadTube - 4 Pin Base - Beveled End TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Initial Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	QT13/27-4P	49241	13	G24q-1	1	50	900	765	58.8	10000	5.0	2700	82
	QT13/30-4P	49242	13	G24q-1	1	50	900	765	58.8	10000	5.0	3000	82
	QT13/35-4P	49243	13	G24q-1	1	50	900	765	58.8	10000	5.0	3500	82
	QT13/41-4P	49244	13	G24q-1	1	50	900	765	58.8	10000	5.0	4100	82
	QT13/50-4P	49245	13	G24q-1	1	50	900	765	58.8	10000	5.0	5000	82
	QT13/65-4P	49246	13	G24q-1	1	50	900	765	58.8	10000	5.0	6500	82
	QT18/27-4P	49247	18	G24q-2	1	50	1150	980	54.4	10000	5.8	2700	82
	QT18/30-4P	49248	18	G24q-2	1	50	1150	980	54.4	10000	5.8	3000	82
	QT18/35-4P	49249	18	G24q-2	1	50	1150	980	54.4	10000	5.8	3500	82
	QT18/41-4P	49250	18	G24q-2	1	50	1150	980	54.4	10000	5.8	4100	82
	QT18/50-4P	49251	18	G24q-2	1	50	1150	980	54.4	10000	5.8	5000	82
	QT18/65-4P	49252	18	G24q-2	1	50	1150	980	54.4	10000	5.8	6500	82
	QT26/27-4P	49253	26	G24q-3	1	50	1710	1460	56.2	10000	6.4	2700	82
	QT26/30-4P	49254	26	G24q-3	1	50	1710	1460	56.2	10000	6.4	3000	82
	QT26/35-4P	49255	26	G24q-3	1	50	1710	1460	56.2	10000	6.4	3500	82
	QT26/41-4P	49256	26	G24q-3	1	50	1710	1460	56.2	10000	6.4	4100	82
	QT26/50-4P	49257	26	G24q-3	1	50	1710	1460	56.2	10000	6.4	5000	82
	QT26/65-4P	49258	26	G24q-3	1	50	1710	1460	56.2	10000	6.4	6500	82

Lamps are dimmable to 10%

LINEAR FLUORESCENT

Fluorescent Lamp Starters

	Ordering Code	Bar Code	Cart. Qty.	Wattage Covered
	FS2	49550	25	14, 15, 20 W
	FS4	49551	25	30, 40 W
	FS5	49552	25	4, 6, 8 W
	FS12	49553	25	32 W
	FSU - 120V	49554	25	4-30 W
	FSU - 220V	49555	25	4-30 W

T5 - Standard TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	F14T5/835	81147	14	G5	1	25	Standard	1350	96.4	35,000*	22	3500	85
	F14T5/841	81148	14	G5	1	25	Standard	1350	96.4	35,000*	22	4100	85
	F21T5/835	81149	21	G5	1	25	Standard	2100	100	35,000*	34	3500	85
	F21T5/841	81150	21	G5	1	25	Standard	2100	100	35,000*	34	4100	85
	F28T5/835	81151	28	G5	1	25	Standard	2900	103.6	35,000*	46	3500	85
	F28T5/841	81152	28	G5	1	25	Standard	2900	103.6	35,000*	46	4100	85

* 35,000 hours w/ 12 hour starts and programmed soft start ballast. 25,000 hours w/ other ballasts and shorter starts.



23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com

LINEAR FLUORESCENT

T5 - High Output TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	F24T5/HO/835	81154	24	G5	1	25	High Output	2000	83.3	35,000*	22	3500	85
	F24T5/HO/841	81155	24	G5	1	25	High Output	2000	83.3	35,000*	22	4100	85
	F39T5/HO/835	81156	39	G5	1	25	High Output	3500	89.7	35,000*	34	3500	85
	F39T5/HO/841	81157	39	G5	1	25	High Output	3500	89.7	35,000*	34	4100	85
	F54T5/HO/835	81158	54	G5	1	25	High Output	5000	92.6	35,000*	46	3500	85
	F54T5/HO/841	81159	54	G5	1	25	High Output	5000	92.6	35,000*	46	4100	85
	F54T5/HO/850	81160	54	G5	1	25	High Output	4850	89.8	35,000*	46	5000	85

* 35,000 hours w/ 12 hour starts and programmed soft start ballast. 25,000 hours w/ other ballasts and shorter starts.

T5 - Miniature Bipin TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	F4T5/CW	15500	4	Min. Bipin - (G5)	1	100	Cool White	135	100	25	6000	6	4100	60
	F4T5/D	15501	4	Min. Bipin - (G5)	1	100	Daylight	115	92	23	6000	6	6500	75
	F4T5/W	15502	4	Min. Bipin - (G5)	1	100	White	140	104	26	6000	6	3500	55
	F6T5/CW	15505	6	Min. Bipin - (G5)	1	50	Cool White	295	235	39.2	7500	9	4100	60
	F6T5/D	15506	6	Min. Bipin - (G5)	1	50	Daylight	230	185	30.8	7500	9	6500	75
	F6T5/W	15508	6	Min. Bipin - (G5)	1	50	White	270	215	35.8	7500	9	3500	55
	F6T5/WW	15507	6	Min. Bipin - (G5)	1	50	Warm White	275	220	36.7	7500	9	3000	52
	F8T5/CW	15510	8	Min. Bipin - (G5)	1	50	Cool White	400	320	40	7500	12	4100	60
	F8T5/D	15511	8	Min. Bipin - (G5)	1	50	Daylight	330	265	33.1	7500	12	6500	75
	F8T5/W	15513	8	Min. Bipin - (G5)	1	50	White	400	320	40	7500	12	3500	55
	F8T5/WW	15512	8	Min. Bipin - (G5)	1	50	Warm White	410	330	41.3	7500	12	3000	52
	F13T5/CW	15517	13	Min. Bipin - (G5)	1	50	Cool White	850	705	54.2	7500	21	4100	60
	F13T5/WW	15518	13	Min. Bipin - (G5)	1	50	Warm White	870	720	55.4	7500	21	3000	60
F13T5/D	15531	13	Min. Bipin - (G5)	1	50	Daylight	700	460	35.4	7500	21	6500	75	

T8 Universal Start - Medium Bipin TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Life	MOL in.	Color Temp.	CRI
	F32T8/730K	49584	32	Med Bipin - (G13)	36	360	Tri Phos 70+ CRI	2850	NA	25,000*	48	3000	75
	F32T8/735K	49585	32	Med Bipin - (G13)	36	360	Tri Phos 70+ CRI	2850	NA	25,000*	48	3500	75
	F32T8/741K	49586	32	Med Bipin - (G13)	36	360	Tri Phos 70+ CRI	2850	NA	25,000*	48	4100	75
	F32T8/830K	49587	32	Med Bipin - (G13)	36	360	Tri Phos 80+ CRI	2950	NA	25,000*	48	3000	83
	F32T8/835K	49588	32	Med Bipin - (G13)	36	360	Tri Phos 80+ CRI	2950	NA	25,000*	48	3500	83
	F32T8/841K	49589	32	Med Bipin - (G13)	36	360	Tri Phos 80+ CRI	2950	NA	25,000*	48	4100	83
	F32T8/850K	81174	32	Med Bipin - (G13)	36	360	Tri Phos 80+ CRI	2950	NA	25,000*	48	5000	83

* 25,000 hours w/ 12 hour starts and programmed soft start ballast. 20,000 hours w/ other ballasts and shorter starts.

T8 - Medium Bipin TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	F10T8/CW	15524	10	Med Bipin - (G13)	1	25	Cool White	480	425	42.5	7500	13	4100	60
	F13T8/CW	15529	13	Med Bipin - (G13)	1	25	Cool White	565	480	36.9	7500	12	4100	60
	F14T8/CW	15519	14	Med Bipin - (G13)	1	25	Cool White	685	580	41.4	7500	15	4100	60
	F14T8/D	15520	14	Med Bipin - (G13)	1	25	Daylight	645	545	38.9	7500	15	6500	75
	F15T8/CW	15521	15	Med Bipin - (G13)	1	25	Cool White	825	725	48.3	7500	18	4100	60
	F15T8/D	15522	15	Med Bipin - (G13)	1	25	Daylight	700	615	41	7500	18	6500	75
	F15T8/W	15525	15	Med Bipin - (G13)	1	25	White	800	725	48.3	7500	18	3500	55
	F15T8/WW	15523	15	Med Bipin - (G13)	1	25	Warm White	845	745	49.7	7500	18	3000	52



23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com

LINEAR FLUORESCENT

T8 Rapid Start - Medium Bipin TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Life	MOL in.	Color Temp.	CRI
	F17T8/730K	49572	17	Med Bipin - (G13)	1	24	Tri Phos 70+ CRI	1325	NA	25,000*	24	3000	75
	F17T8/735K	49573	17	Med Bipin - (G13)	1	24	Tri Phos 70+ CRI	1325	NA	25,000*	24	3500	75
	F17T8/741K	49574	17	Med Bipin - (G13)	1	24	Tri Phos 70+ CRI	1325	NA	25,000*	24	4100	75
	F17T8/830K	49575	17	Med Bipin - (G13)	1	24	Tri Phos 80+ CRI	1400	NA	25,000*	24	3000	83
	F17T8/835K	49576	17	Med Bipin - (G13)	1	24	Tri Phos 80+ CRI	1400	NA	25,000*	24	3500	83
	F17T8/841K	49577	17	Med Bipin - (G13)	1	24	Tri Phos 80+ CRI	1400	NA	25,000*	24	4100	83
	F17T8/850K	48055	17	Med Bipin - (G13)	1	24	Tri Phos 80+ CRI	1400	NA	25,000*	24	5000	83
	F25T8/730K	49578	25	Med Bipin - (G13)	1	24	Tri Phos 70+ CRI	2125	NA	25,000*	36	3000	75
	F25T8/735K	49579	25	Med Bipin - (G13)	1	24	Tri Phos 70+ CRI	2125	NA	25,000*	36	3500	75
	F25T8/741K	49580	25	Med Bipin - (G13)	1	24	Tri Phos 70+ CRI	2125	NA	25,000*	36	4100	75
	F25T8/830K	49581	25	Med Bipin - (G13)	1	24	Tri Phos 80+ CRI	2225	NA	25,000*	36	3000	83
	F25T8/835K	49582	25	Med Bipin - (G13)	1	24	Tri Phos 80+ CRI	2225	NA	25,000*	36	3500	83
	F25T8/841K	49583	25	Med Bipin - (G13)	1	24	Tri Phos 80+ CRI	2225	NA	25,000*	36	4100	83
	F28T8/830K	05264	28	Med Bipin - (G13)	1	36	Tri Phos 80+ CRI	2800	NA	25,000*	48	3000	83
	F28T8/835K	05265	28	Med Bipin - (G13)	1	36	Tri Phos 80+ CRI	2800	NA	25,000*	48	3500	83
F28T8/841K	05266	28	Med Bipin - (G13)	1	36	Tri Phos 80+ CRI	2800	NA	25,000*	48	4100	83	
F28T8/850K	05267	28	Med Bipin - (G13)	1	36	Tri Phos 80+ CRI	2800	NA	25,000*	48	5000	83	

* 25,000 hours w/ 12 hour starts and programmed soft start ballast. 20,000 hours w/ other ballasts and shorter starts.

T12 - Medium Bipin TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	F34T12/CW/RW	50141	34	Med Bipin - (G13)	1	30	Cool White	2650	2300	77.9	20000	48	4100	63

CIRCULINE & U-BEND FLUORESCENT

Circuline T9 Rapid Start TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	FC8T9/CW	15604	22	4-Pin (G10q)	1	20	Circuline	1100	825	37.5	12000	8-1/4	4100	60
	FC8T9/D	15532	22	4-Pin (G10q)	1	20	Circuline	925	690	31.4	12000	8-1/4	6500	75
	FC12T9/CW	15606	32	4-Pin (G10q)	1	20	Circuline	1950	1460	45.6	12000	12	4100	60
	FC12T9/D	15533	32	4-Pin (G10q)	1	20	Circuline	1675	1260	39.4	12000	12	6500	75
	FC16T9/CW	15534	40	4-Pin (G10q)	1	20	Circuline	2700	2030	50.8	12000	16	4100	60
FC16T9/D	15535	40	4-Pin (G10q)	1	20	Circuline	2250	1690	42.3	12000	16	6500	75	

U-Bend 1 5/8" TCLP Compliant

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Init. Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	F31T8/830/U	05287	31	Bi-pin	1	20	2750	2475	88.7	20,000	22.5	3000K	84
	F31T8/835/U	05288	31	Bi-pin	1	20	2750	2475	88.7	20,000	22.5	3500K	84
	F31T8/841/U	05289	31	Bi-pin	1	20	2750	2745	88.7	20,000	22.5	4100K	84
F31T8/850/U	05290	31	Bi-pin	1	20	2625	2365	88.7	20,000	22.5	5000K	84	




23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com


CIRCULINE & U-BEND FLUORESCENT

U-Bend 6" TCLP Compliant


	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Init. Lum.	Mean Lum.	Lum/Watt	Life	MOL in.	Color Temp.	CRI
	F32T8/735K/U6	49590	32	G13	1	20	2650	2370	82.8	20000	22.5	3500K	75
	F32T8/741K/U6	02401	32	G13	1	20	2650	2370	82.8	20000	22.5	4100K	75
	F32T8/750K/U6	02402	32	G13	1	20	2600	2325	86.3	20000	22.5	5000K	75
	F32T8/835K/U6	02403	32	G13	1	20	2800	2535	87.5	20000	22.5	3500K	85
	F32T8/841K/U6	02404	32	G13	1	20	2800	2535	87.5	20000	22.5	4100K	85
	F32T8/850K/U6	02405	32	G13	1	20	2750	2500	85.9	20000	22.5	5000K	85

GERMICIDAL LINEAR FLUORESCENT


T5 - Miniature Bipin - Black Light & Black Light Blue (Peak Emission 365 nm)

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Life	MOL in.	Color Temp.	CRI
	F4T5/BL	15503	4	Min. Bipin - (G5)	1	100	Black Light	N/A	N/A	6000	6	N/A	N/A
	F4T5/BLB	15504	4	Min. Bipin - (G5)	1	100	Black Light Blue	N/A	N/A	6000	6	N/A	N/A
	F6T5/BL	15528	6	Min. Bipin - (G5)	1	50	Black Light	N/A	N/A	7500	9	N/A	N/A
	F6T5/BLB	15509	6	Min. Bipin - (G5)	1	50	Black Light Blue	N/A	N/A	7500	9	N/A	N/A
	F8T5/BL	15515	8	Min. Bipin - (G5)	1	50	Black Light	N/A	N/A	7500	12	N/A	N/A
	F8T5/BLB	15516	8	Min. Bipin - (G5)	1	50	Black Light Blue	N/A	N/A	7500	12	N/A	N/A


T8 - Medium Bipin - Black Light & Black Light Blue (Peak Emission 365 nm)

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Life	MOL in.	Color Temp.	CRI
	F15T8/BL	15526	15	Med Bipin - (G13)	1	25	Black Light	N/A	N/A	7500	18	N/A	N/A
	F15T8/BLB	15527	15	Med Bipin - (G13)	1	25	Black Lt. Blue	N/A	N/A	7500	18	N/A	N/A


T5 - Miniature Bipin - Aquarium (Peak Emission 658 nm)

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Life	MOL in.	Color Temp.	CRI
	F8T5/AQ	15514	8	Min. Bipin - (G5)	1	50	Aquarium	100	90	7500	12	N/A	N/A

T8 - Medium Bipin - Aquarium

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Description	Init. Lum.	Mean Lum.	Life	MOL in.	Color Temp.	CRI
	F15T8/AQ	15530	15	Med Bipin - (G13)	1	25	Aquarium	240	216	7500	18	N/A	67

Germicidal Lamps - T5, T6, T8, T10 (Peak Emission 254 nm)

	Ordering Code	Bar Code	Watts	Base	Pkg. Qty.	Cart. Qty.	Bulb	Special Desc.	Life	MOL mm	MOD mm
	G4T5	41300	4	G5	1	50	T-5	Germicidal (254nm), Preheat	6000	134.5	15.5
	G6T5	41302	6	G5	1	50	T-5	Germicidal (254nm), Preheat	6000	210.5	15.5
	G8T5	41384	8	G5	1	50	T-5	Germicidal (254nm), Preheat	6000	287.0	15.5
	G10T8	41386	10	G13	1	50	T-8	Germicidal (254nm), Preheat	6000	330	25.5
	G15T8	41388	15	G13	1	50	T-8	Germicidal (254nm), Preheat	8000	436	25.5
	G20T10	00202	20	G13	1	50	T-10	Germicidal (254nm), Preheat	8000	588.5	32.5
	G25T8	00203	25	G13	1	50	T-8	Germicidal (254nm), Preheat	8000	436	25.5
	G30T8	00204	30	G13	1	50	T-8	Germicidal (254nm), Preheat	8000	893	25.5
	G40T10	00214	40	G13	1	50	T-10	Germicidal (254nm), Preheat	8000	1198	32.5
	GTL-2	00215	2	E17	1	50	T-6	Germicidal (254nm), Preheat	2000	55	20
	GTL3	41568	3	E17	1	50	T-6	Germicidal (254nm), Preheat	2000	63	20