




23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com


R & BR INCANDESCENT

R20

	Ordering Code	Bar Code	Watts	Volts	Bulb Type	Base	Life	Lum.	Finish	MOL in.	Beam Pattern
	30R20/FL-120V	49791	30	120	R20	MED	2000	245	Frost	3 1/16	Flood
	30R20/FL-130V*	49792	30	130	R20	MED	2000*	245	Frost	3 1/16	Flood
	30R20/SP-130V*	49793	30	130	R20	MED	2000*	245	Clear	3 1/16	Spot
	50R20/FL-120V	49794	50	120	R20	MED	2000	400	Frost	3 1/16	Flood
	50R20/SP-120V	49810	50	120	R20	MED	2000	400	Clear	3 1/16	Spot
	50R20/FL-130V*	49795	50	130	R20	MED	2000*	400	Frost	3 1/16	Flood
	50R20/SP-130V*	49796	50	130	R20	MED	2000*	400	Clear	3 1/16	Spot


* 130 volt lamps are rated at **5,000** hours when operated at 120 volts.

BR30

	Ordering Code	Bar Code	Watts	Volts	Bulb Type	Base	Life	Lum.	Finish	MOL in.	Beam Pattern
	45BR30/FL-120V	49797	45	120	BR30	MED	2000	390	Frost	5 3/8	Flood
	65BR30/FL-120V	49798	65	120	BR30	MED	2000	650	Frost	5 3/8	Flood
	65BR30/SP-120V	49811	65	120	BR30	MED	2000	650	Clear	5 3/8	Spot
	65BR30/FL-130V*	49799	65	130	BR30	MED	2000*	650	Frost	5 3/8	Flood
	65BR30/SP-130V*	49800	65	130	BR30	MED	2000*	650	Clear	5 3/8	Spot
	75BR30/FL-120V	00298	75	120	BR30	MED	2000	675	Frost	5 3/8	Flood

* 130 volt lamps are rated at **5,000** hours when operated at 120 volts.


BR40

	Ordering Code	Bar Code	Watts	Volts	Bulb Type	Base	Life	Lum.	Finish	MOL in.	Beam Pattern
	65BR40/FL-120V	49801	65	120	BR40	MED	2000	650	Frost	6 9/16	Flood
	65BR40/FL-130V*	49802	65	130	BR40	MED	2000*	650	Frost	6 9/16	Flood
	75BR40/FL-120V	00299	75	120	BR40	MED	2000	675	Frost	6 9/16	Flood
	120BR40/FL-120V	49803	120	120	BR40	MED	2000	1200	Frost	6 9/16	Flood
	120BR40/SP-120V	49812	120	120	BR40	MED	2000	1200	Clear	6 9/16	Spot
	120BR40/FL-130V*	49804	120	130	BR40	MED	2000*	1200	Frost	6 9/16	Flood
	120BR40/SP-130V*	49805	120	130	BR40	MED	2000*	1200	Clear	6 9/16	Spot


* 130 volt lamps are rated at **5,000** hours when operated at 120 volts.

A-LINE INCANDESCENT

A-15

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Filament	MOL in/ mm	MOD in/ mm	Avg. Life	Coating
	40A15-130V	44390	A-15	E26	130	40	C-2V	3.50/88.9	1.88/47.7	1500	Clear
	40A15/F-130V	44392	A-15	E26	130	40	C-2V	3.50/88.9	1.88/47.7	1500	Frosted
	40A15-230/250V	44394	A-15	E26	230-250	40	C-2F	3.50/88.9	1.88/47.7	1500	Clear
	40A15/F-230/250V	44396	A-15	E26	230-250	40	C-2F	3.50/88.9	1.88/47.7	1500	Frosted

A-15 Fan Bulb VIBRATION RESISTANT

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Filament	MOL in.	MOD in.	Avg. Life	Coating
	40A15CL/RS-130V*	00292	A-15	E26	130	40	C-9	3.5	1.9	2500	Clear
	40A15W/RS-130V*	00293	A-15	E26	130	40	C-9	3.5	1.9	2500	White
	60A15CL/RS-130V*	00294	A-15	E26	130	40	C-9	3.5	1.9	2500	Clear
	60A15W/RS-130V*	00295	A-15	E26	130	40	C-9	3.5	1.9	2500	White

* 130 volt lamps are rated at **6,000** hours when operated at 120 volts.




23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com

A-LINE INCANDESCENT


A-19



Ordering Code	Bar Code	Watts	Volts	Bulb Type	Base	Life	Lum.	Lum/Watt	Filament	Finish	MOL in.	Pkg. Qty.	Cart. Qty.
40A-130V*	49819	40	130	A19	Medium	2000*	380	9.5	CC-6	Frost	4.43	4	120
40A/CL-130V*	49846	40	130	A19	Medium	2000*	390	9.75	CC-6	Clear	4.43	4	120
60A-130V*	49823	60	130	A19	Medium	2000*	690	11.5	CC-6	Frost	4.43	4	120
60A/CL-130V*	49848	60	130	A19	Medium	2000*	700	11.67	CC-6	Clear	4.43	4	120
60A/SW-130V*	49849	60	130	A19	Medium	2000*	660	14	CC-6	Soft White	4.43	4	120
75A-130V*	49825	75	130	A19	Medium	2000*	890	11.87	CC-6	Frost	4.43	4	120
75A/CL-130V*	49850	75	130	A19	Medium	2000*	900	12	CC-6	Clear	4.43	4	120
75A/SW-130V*	49851	75	130	A19	Medium	2000*	850	15.33	CC-6	Soft White	4.43	4	120
100A-130V*	49827	100	130	A19	Medium	2000*	1270	12.7	CC-6	Frost	4.43	4	120
100A/CL-130V*	49852	100	130	A19	Medium	2000*	1290	12.9	CC-6	Clear	4.43	4	120
150A-130V*	49854	150	130	A23	Medium	2000*	2800	18.67	CC-6	Frost	5.37	1	60

* 130 volt lamps are rated at 5,000 hours when operated at 120 volts.

Rough Service




Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Lumens	Filament	MOL in/mm	MOD in/mm	Avg. Life	Coating
50A/RS-12V	15812	A-19	E26	12	50	500	C-6	4.44/112.8	2.38/60.3	2500	Frosted
75A/RS-12V	15814	A-19	E26	12	75	750	C-6	4.44/112.8	2.38/60.3	2500	Frosted
100A/RS-12V	15816	A-19	E26	12	100	1100	C-6	4.44/112.8	2.38/60.3	2500	Frosted
50A/RS	15800	A-19	E26	130	50	500	C-9	4.44/112.8	2.38/60.3	2500	Frosted
75A/RS	15802	A-19	E26	130	75	750	C-9	4.44/112.8	2.38/60.3	2500	Frosted
100A/RS	15804	A-19	E26	130	100	1100	C-9	4.44/112.8	2.38/60.3	2500	Frosted
50A/RS/TF	15806	A-19	E26	130	50	500	C-9	4.44/112.8	2.38/60.3	2500	Silicone Coated
75A/RS/TF	15808	A-19	E26	130	75	750	C-9	4.44/112.8	2.38/60.3	2500	Silicone Coated
100A/RS/TF	15810	A-19	E26	130	100	1100	C-9	4.44/112.8	2.38/60.3	2500	Silicone Coated
150A/RS	00008	A-21	E26	130	150	1650	C-9	4.96/126	2.63/66.7	2500*	Frosted

* Rated at 5,000 hours when operated at 120 volts.

DECORATIVE INCANDESCENT


Globe



Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Filament	MOL in.	MOD in.	Avg. Life	Coating
25G16.5/CL-130V	00270	G16.5	CS	130	25	C-7A	4.4	2.1	1500	Clear
25G16.5/W-130V	00271	G16.5	CS	130	25	C-7A	4.4	2.1	1500	White
40G16.5/CL-130V	00272	G16.5	CS	130	40	CC-2V	4.4	2.1	1500	Clear
40G16.5/W-130V	00273	G16.5	CS	130	40	CC-2V	4.4	2.1	1500	White
40G25/CL-130V*	00274	G25	MED	130	40	CC-9	6.75	2.1	1500	Clear
40G25/W-130V*	00275	G25	MED	130	40	CC-9	6.75	2.1	1500	White
60G25/CL-130V*	00276	G25	MED	130	60	CC-9	6.75	2.1	1500	Clear
60G25/W-130V*	00277	G25	MED	130	60	CC-9	6.75	2.1	1500	White

* 130 volt lamps are rated at 4,000 hours when operated at 120 volts.

Torpedo



Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Filament	MOL in.	MOD in.	Avg. Life	Coating
15B9.5/CL-130V	00278	B9.5	CS	130	15	C-7A	3.5	1.2	1500	Clear
15B9.5-130V	00279	B9.5	CS	130	15	C-7A	3.5	1.2	1500	Frost
25B9.5/CL-130V	00281	B9.5	CS	130	25	CC-2V	3.5	1.2	1500	Clear
25B9.5-130V	00282	B9.5	CS	130	25	CC-2V	3.5	1.2	1500	Frost
40B9.5/CL-130V	00283	B9.5	CS	130	40	CC-2V	3.5	1.2	1500	Clear
40B9.5-130V	00284	B9.5	CS	130	40	CC-2V	3.5	1.2	1500	Frost

* 130 volt lamps are rated at 4,000 hours when operated at 120 volts.