





23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com






QUARTZ HEAT

Tubular Heat (Continued)

 	Ordering Code	Bulb	Base	Volts	Watts	MOL in/mm	MOD in/mm	Filament	Color Temp.	Avg. Life	Special Description
	17032	T-3	R7s		200-220	1600	19.63/498.5	0.40/10.0	C-8	2400	5000
17034	T-3	R7s		230-250	1600	19.63/498.5	0.40/10.0	C-8	2400	5000	Frosted
17040	T-3	6" Leads		230-250	2000	13.78/350.0	0.40/10.0	C-8	2400	5000	Clear, High Temp. Construction
17042	T-3	6" Leads		460-500	2500	28.82/732	0.40/10.0	C-8	2400	5000	Frosted
17044	T-3	R7s		460-500	2500	28.62/727	0.40/10.0	C-8	2400	5000	Frosted
17046	T-3	6" Leads		460-500	2500	28.82/732	0.40/10.0	C-8	2400	5000	Clear
17048	T-3	6" Leads		480	3650	41.6/1057	0.40/10.0	C-8	2400	5000	Clear
17050	T-3	6" Leads		550-600	3800	41.8/1062	0.40/10.0	C-8	2400	5000	Frosted
17052	T-3	6" Leads		550-600	3800	41.8/1062	0.40/10.0	C-8	2400	5000	Clear, Vertical Burn

HALOGEN MINIATURE


Halogen Miniatures

 G4  BA9s  P13.5s  BA15s  BAY15d	Ordering Code	Base	Volts	Amps	Lumens or CP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Description
	787	G4		6.0	1.67	16cp	C-6	1.00/25.4	0.30/7.6	100
788	G4		6.0	3.33	32cp	C-6	1.00/25.4	0.30/7.6	100	
891	G4		12.8	8W	11.5cp	C-6	1.20/30.5	0.32/8.1	500	
778	G4		6.0	3.33	32cp	C-6	1.05/26.7	0.38/9.6	100	
789	G4		12.0	1.17	22cp	C-6	1.05/26.7	0.38/9.6	200	
64111	BA9s		12.0	0.416	6.7cp	C-6	1.29/32.8	0.38/9.6	240	
HPR52	P13.5s		2.8	0.85	35	C-6	1.25/31.8	0.38/9.6	10	Flashlight
HPR53	P13.5s		4.0	0.85	48	C-6	1.25/31.8	0.38/9.6	25	Flashlight
HPR44	P13.5s		4.0	1.00	54	C-6	1.25/31.8	0.38/9.6	300	Flashlight
HPR55	P13.5s		5.2	0.50	48	C-6	1.25/31.8	0.38/9.6	15	Flashlight
HPR50	P13.5s		5.2	0.85	85	C-6	1.25/31.8	0.38/9.6	25	Flashlight
HPR36	P13.5s		5.5	1.00	93	C-6	1.25/31.8	0.38/9.6	40	Flashlight
HPR40	P13.5s		6.0	0.67	75	C-6	1.25/31.8	0.38/9.6	50	Flashlight
HPR51	P13.5s		6.5	0.70	90	C-6	1.25/31.8	0.38/9.6	25	Flashlight
796	BA15s		12.8	35W	60cp	C-6	2.50/63.5	0.48/12.2	300	Halogen
795	BA15s		12.8	50W	108cp	C-6	2.50/63.5	0.48/12.2	200	Halogen
795X	BA15s		12.8	50W	108cp	C-8	2.50/63.5	0.48/12.2	200	Halogen
H1156	BA15s		12.8	50W	108cp	C-6	2.50/63.5	0.56/14.2	250	Halogen
H1157	BAY15d		12.8	50/15W	108/24cp	C-6/C-6	2.00/50.8	.64/16.3	250/400	Halogen


EiKO stocks over 1500 different miniature lamps.
Please refer to the our website at: www.eiko-ltd.com for complete information.

BASED LED

S-8 BAY15d (DC Index Bayonet) Base

	Ordering Code	Old EiKO #	Bar Code	Volts	MOL in/mm	MOD in/mm	LED Type	Color	View Angle °	Replaces
	LED-12-DCBAY-W	N/A		00343	12AC/DC	1.81/46	1.0/25	Cluster	White	25°
LED-12-DCBAY-R	N/A		00344	12AC/DC	1.81/46	1.0/25	Cluster	Red	25°	DC Index Bayonet Base 12V S8

S-8 BA15s (SC Bayonet) Base

	Ordering Code	Old EiKO #	Bar Code	Volts	MOL in/mm	MOD in/mm	LED Type	Color	View Angle °	Replaces
	LED-12-SCBAY-W	N/A		00341	12VAC/DC	1.81/46	1.0/25	Cluster	White	30°
LED-12-SCBAY-R	N/A		00342	12VAC/DC	1.81/46	1.0/25	Cluster	Red	30°	SC Bayonet Base 12V S8




23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679


www.eiko.com
eiko@eiko.com

BASED LED


SV.5 Festoon Base

	Ordering Code	Old EiKO #	Bar Code	Volts	MOL in/ mm	MOD in/ mm	LED Type	Color	View Angle °	Replaces
	LED-12-FESTOON-W	N/A			12VDC	1.73/44	0.43/11	Cluster	White	30°
LED-24-FESTOON-W	N/A			24VDC	1.73/44	0.43/11	Cluster	White	30°	10x44 Xenon


T-3¼ BA9S (Miniature Bayonet) Base

	Ordering Code	Old EiKO #	Bar Code	Volts	MOL in/ mm	MOD in/ mm	LED Type	Color	View Angle °	Replaces
	LED-6-BA9S-W			05742	6 AC/DC	1.0/25	0.40/10	Single	White	18°
LED-14-BA9S-G	3573.09.144-003	81196	81196	14AC/DC	1.0/25	0.4/10	Single	Green	18°	756, 1813, 1815, 1816, 1889, 1891, 1892, 1893
LED-14-BA9S-R	1573.09.144-004	81197	81197	14AC/DC	1.0/25	0.4/10	Single	Red	18°	756, 1813, 1815, 1816, 1889, 1891, 1892, 1893
LED-14-BA9S-W	5100.09.144-004	81198	81198	14AC/DC	1.0/25	0.4/10	Single	White	18°	756, 1813, 1815, 1816, 1889, 1891, 1892, 1893
LED-24-BA9S-G	3573.09.128-002	81200	81200	24-28AC/DC	1.0/25	0.4/10	Single	Green	18°	24MB, 28MB, 313, 757, 1818, 1819, 1820, 1829, 1843, 1864, 1873
LED-24-BA9S-R	1573.09.128-002	81201	81201	24-28AC/DC	1.0/25	0.4/10	Single	Red	18°	24MB, 28MB, 313, 757, 1818, 1819, 1820, 1829, 1843, 1864, 1873
LED-24-BA9S-W	5100.09.128-002	81202	81202	24-28AC/DC	1.0/25	0.4/10	Single	White	18°	24MB, 28MB, 313, 757, 1818, 1819, 1820, 1843, 1829, 1864, 1873
LED-120-MB-G	3573.09.537-002	81188	81188	110-130VAC	1.0/25	0.4/10	Single	Green	18°	120MB, 120MB-6, 130MB, 8-3995, 949, 967
LED-120-MB-R	1573.09.537-002	81189	81189	110-130VAC	1.0/25	0.4/10	Single	Red	18°	120MB, 120MB-6, 130MB, 8-3995, 949, 967
LED-120-MB-W	5100.09.537-002	81190	81190	110-130VAC	1.0/25	0.4/10	Single	White	18°	120MB, 120MB-6, 130MB, 8-3995, 949, 967
LED-120-MB-Y	2513.09.537-002	81191	81191	110-130VAC	1.0/25	0.4/10	Single	Yellow	18°	120MB, 120MB-6, 130MB, 8-3995, 949, 967


T-1¾ Midget Flange Base

	Ordering Code	Old EiKO #	Bar Code	Volts	MOL in/ mm	MOD in/ mm	LED Type	Color	View Angle °	Replaces
	LED-24-MF-R	3021.06.128-003	81204	81204	24-28AC/DC	0.63/16.0	0.24/6	Single	Red	40°
LED-24-MF-W	3100.06.128-004	81205	81205	24-28AC/DC	0.63/16.0	0.24/6	Single	White	40°	327, 376, 385, 387, 7341
LED-24-MF-Y	3121.06.128-003	81206	81206	24-28AC/DC	0.63/16.0	0.24/6	Single	Yellow	40°	327, 376, 385, 387, 7341

T-1¾ Midget Groove Base

	Ordering Code	Old EiKO #	Bar Code	Volts	MOL in/ mm	MOD in/ mm	LED Type	Color	View Angle °	Replaces
	LED-24-MG-R	3021.57.128-002	81207	81207	24-28 AC/DC	0.63/16.0	0.24/6	Single	Red	40°
LED-24-MG-W	3100.57.128-002	81208	81208	24-28 AC/DC	0.63/16.0	0.24/6	Single	White	40°	334, 388
LED-24-MG-Y	3121.57.128-002	81209	81209	24-28 AC/DC	0.63/16.0	0.24/6	Single	Yellow	40°	334, 388

T-1¾ Sub Miniature Wedge Base

	Ordering Code	Old EiKO #	Bar Code	Volts	MOL in/ mm	MOD in/ mm	LED Type	Color	View Angle °	Replaces
	LED-6-T1.75WEDGE-R	3021.01.105-002	81218	81218	6AC/DC	0.77/19.4	0.22/5.5	Single	Red	100°
LED-6-T1.75WEDGE-W	3100.01.105-002	81219	81219	6AC/DC	0.77/19.4	0.22/5.5	Single	White	100°	56, 79, 84, 86
LED-6-T1.75WEDGE-Y	3121.01.105-002	81220	81220	6AC/DC	0.77/19.4	0.22/5.5	Single	Yellow	100°	56, 79, 84, 86
LED-14-T1.75WEDGE-W	3100.01.144-003	81199	81199	14AC/DC	0.77/19.4	0.22/5.5	Single	White	100°	18, 37, 70, 73, 74
LED-24-T1.75WEDGE-G	3221.01.128-503	81215	81215	24-28AC/DC	0.77/19.4	0.22/5.5	Single	Green	100°	17, 85
LED-24-T1.75WEDGE-R	3021.01.128-503	81215	81215	24-28AC/DC	0.77/19.4	0.22/5.5	Single	Red	100°	17, 85
LED-24-T1.75WEDGE-W	3100.01.128-503	81216	81216	24-28AC/DC	0.77/19.4	0.22/5.5	Single	White	100°	17, 85
LED-24-T1.75WEDGE-Y	3121.01.128-503	81217	81217	24-28AC/DC	0.77/19.4	0.22/5.5	Single	Yellow	100°	17, 85



23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com

BASED LED

T-2 Slide Base 5



Ordering Code	Old Eiko #	Bar Code	Volts	MOL in/mm	MOD in/mm	LED Type	Color	View Angle °	Replaces
LED-24-PSB-G	3221.47.128-003	81211	24-28AC/DC	1.1/28	0.27/6.8	Single	Green	100°	24PSB5, 28PSB5
LED-24-PSB-R	3021.47.128-002	81210	24-28AC/DC	1.1/28	0.27/6.8	Single	Red	100°	24PSB5, 28PSB5
LED-24-PSB-W	3100.47.128-002	81212	24-28AC/DC	1.1/28	0.27/6.8	Single	White	100°	24PSB5, 28PSB5
LED-24-PSB-Y	3121.47.128-003	81213	24-28AC/DC	1.1/28	0.27/6.8	Single	Yellow	100°	24PSB5, 28PSB5
LED-120-PSB-G	5313.47.537-002	81194	110-130VAC	1.1/28	0.27/6.8	Single	Green	100°	120PSB5, 120PSB-Neon
LED-120-PSB-R	1313.47.537-002	81192	110-130VAC	1.1/28	0.27/6.8	Single	Red	100°	120PSB5, 120PSB-Neon
LED-120-PSB-W	3100.47.565-002	81195	110-130VAC	1.1/28	0.27/6.8	Single	White	100°	120PSB5, 120PSB-Neon
LED-120-PSB-Y	3121.47.537-002	81193	110-130VAC	1.1/28	0.27/6.8	Single	Yellow	100°	120PSB5, 120PSB-Neon


T-3¼ Miniature Wedge Base



Ordering Code	Old Eiko #	Bar Code	Volts	MOL in/mm	MOD in/mm	LED Type	Color	View Angle °	Replaces
LED-194-R	N/A	00346	14AC/DC	1.1/28	.40/10	Single	Red	30°	T 3¼ Min Wedge Based 1¼ V
LED-194-W	N/A	00345	14AC/DC	1.1/28	.40/10	Single	White	30°	T 3¼ Min Wedge Based 1¼ V

LED PAR & MR16

LED PAR & MR16



Ordering Code	Input	Power Consump.	Avg. Life Hours	Luminous Flux	Color Temp.	Beam Angle	Base
LEDP/MR16-FL-30K	12 VAC	5 W	50,000	160 lm.	3000	120°	GU5.3
LEDP/MR16-FL-60K	12 VAC	5 W	50,000	180 lm.	6000	120°	GU5.3
LEDP/MR16-SP-30K	12 VAC	5 W	50,000	160 lm.	3000	60°	GU5.3
LEDP/MR16-SP-60K	12 VAC	5 W	50,000	180 lm.	6000	60°	GU5.3
LEDP/PAR30LN-FL-30K	100~240 VAC	12 W	50,000	260 lm.	3000	120°	E26
LEDP/PAR30LN-FL-60K	100~240 VAC	12 W	50,000	320 lm.	6000	120°	E26
LEDP/PAR30LN-SP-30K	100~240 VAC	12 W	50,000	260 lm.	3000	60°	E26
LEDP/PAR30LN-SP-60K	100~240 VAC	12 W	50,000	320 lm.	6000	60°	E26
LEDP/PAR38-FL-30K	100~240 VAC	18 W	50,000	300 lm.	3000	120°	E26
LEDP/PAR38-FL-60K	100~240 VAC	18 W	50,000	380 lm.	6000	120°	E26
LEDP/PAR38-SP-30K	100~240 VAC	18 W	50,000	300 lm.	3000	60°	E26
LEDP/PAR38-SP-60K	100~240 VAC	18 W	50,000	380 lm.	6000	60°	E26

LED STRING LIGHTS

LED String Lights



Ordering Code	Lamps	Color	Length (ft.)
LEDC6-70B	70	Blue	24
LEDC6-70G	70	Green	24
LEDC6-70R	70	Red	24
LEDC6-70M	70	Multicolor	24
LEDC6-70W	70	White	24

LAMPS BY ANSI CODE

Lamps by ANSI Code

Ordering Code	Base	Volts	Watts	Avg. Life	Possible Sub	Ordering Code	Base	Volts	Watts	Avg. Life	Possible Sub
BAB	GU5.3	12	20	3000	ESX	BFE	P28s	120	750	200	BFK
BAB-BLACK	GU5.3	12	20	3000		BFK/BFL	P28s	120	750	200	BFE
BAB-FG	GU5.3	12	20	3000	ESX-FG	BFM	E14	120	25	500	
BAB-SILVER	GU5.3	12	20	3000		BGB/BGK	P30d	4	0.75A	50	
BAK	P30s	4	0.75A	200	BRS	BHB	G7.9	120	250	25	
BBA	E26	120	250	3		BKV	BA15s	120	30	50	BLR
BCA	E26	120	250	3		BLC	BA15d	120	30	50	
BCK	G17t	120	500	50	CZA/CZB	BLK	E12	120	30	50	BLR

Continued on next page ►►