



23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679

www.eiko.com  
eiko@eiko.com

## HEALTH CARE

### Health Care (Continued)

Ordering Code	Base	Volts	Watts	Avg. Life	Ordering Code	Base	Volts	Watts	Avg. Life
FDX	GY6.35 w/ Ceramic Seal Cover	12	100	50	JCR/M12V75W	G5.3	12	75	50
G10T8	G13	-	10	6000	JCR/M14V35W	GU4	14	35	50
G15T8	G13	-	15	8000	P129362-228	GY9.5	22.8	220	500
G4T5	G5	-	4	7500	Q75CL-28V	E10	28	75	2000
G6T5	G5	-	6	7500	Q75CL/DC-28V	BA15d	28	75	2000
G8T5	G5	-	8	7500	Q150T4/CL/25	R7s	25	150	3000
JC12V50WH20	G6.35	12	50	2000	Q235T4/3-33V	GY9.5	33	235	500
JCR/M12V100W	G5.3	12	100	50	Q250CL/MC-120V	E11	120	250	2000

See Cross-Referencing Section on pages 10-13.

## MINIATURE

### B-3½ Single Contact Miniature Flanged Base

Ordering Code	Bar Code	Bulb	Base	Volts	Amps	Filament	MOL in/mm	MOD in/mm	Avg. Life	Replaces	Description	Typical Use
KPR4	44003	B-3 1/2	P13.5s	2.2	0.47	C-2R	1.25/31.8	0.45/11.5	15		Krypton	
PR4	40108	B-3 1/2	P13.5s	2.33	0.27	C-2R	1.25/31.8	0.45/11.5	10			2"C Cells
PR2	40100	B-3 1/2	P13.5s	2.38	0.5	C-2R	1.25/31.8	0.45/11.5	15			2"D Cells
KPR2	40041	B-3 1/2	P13.5s	2.38	0.5	C-2R	1.25/31.8	0.45/11.5	15	K2	Krypton	
KPR102	40047	B-3 1/2	P13.5s	2.4	0.7	C-2R	1.25/31.8	0.45/11.5	15	K1	Krypton	
PR6	40112	B-3 1/2	P13.5s	2.47	0.3	C-2R	1.25/31.8	0.45/11.5	30			2"D Industrial Cells
PR9	40116	B-3 1/2	P13.5s	2.7	0.15	C-2R	1.25/31.8	0.45/11.5	45			2"D Cells
PR3	40104	B-3 1/2	P13.5s	3.57	0.5	C-2R	1.25/31.8	0.45/11.5	15			3"D Cells
KPR103	40049	B-3 1/2	P13.5s	3.6	0.75	C-2R	1.25/31.8	0.45/11.5	15		Krypton	
KPR3	40043	B-3 1/2	P13.5s	3.6	0.91	C-2R	1.25/31.8	0.45/11.5	30	K3	Krypton	
PR7	40114	B-3 1/2	P13.5s	3.7	0.3	C-2R	1.25/31.8	0.45/11.5	30			3"D Industrial Cells
PR30	40106	B-3 1/2	P13.5s	3.75	0.86	C-2R	1.25/31.8	0.45/11.5	40			Rechargeable 3.75V
KPR130	40055	B-3 1/2	P13.5s	3.85	1.2	C-2R	1.25/31.8	0.45/11.5	20		Krypton	
PR13	40086	B-3 1/2	P13.5s	4.75	0.5	C-2R	1.25/31.8	0.45/11.5	15			6.0V Lantern
KPR13	40045	B-3 1/2	P13.5s	4.75	0.5	C-2R	1.25/31.8	0.45/11.5	10	K13	Krypton	
K15	40061	B-3 1/2	P13.5s	4.8	0.7	C-2R	1.25/31.8	0.45/11.5	15		Krypton	
PR15	40090	B-3 1/2	P13.5s	4.82	0.5	C-2R	1.25/31.8	0.45/11.5	30			6.0V Lantern
PR12	40084	B-3 1/2	P13.5s	5.95	0.5	C-2R	1.25/31.8	0.45/11.5	15			5"D Cells
K12	40059	B-3 1/2	P13.5s	5.95	0.7	C-2R	1.25/31.8	0.45/11.5	15		Krypton	
KPR118	40051	B-3 1/2	P13.5s	7.2	0.55	C-2R	1.25/31.8	0.45/11.5	20	K18	Krypton	
PR18	40096	B-3 1/2	P13.5s	7.2	0.55	C-2R	1.25/31.8	0.45/11.5	3			6"D Cells
PR20	40102	B-3 1/2	P13.5s	8.63	0.5	C-2R	1.25/31.8	0.45/11.5	15			7"D Cells
PR16	40092	B-3 1/2	P13.5s	12.5	0.25	C-2R	1.25/31.8	0.45/11.5	50			Hand Spot 12.5V



### B-6 Single Contact Bayonet Base

Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Description
1003	40155	B-6	SC Bayonet	12.8	0.94	15	C-6	1.75/44.5	0.79/20.1	200	
105	40163	B-6	SC Bayonet	12.8	1.0	12	C-6	1.75/44.5	0.79/20.1	500	
1309	40250	B-6	SC Bayonet	28	0.52	15	2C-6	1.75/44.5	0.79/20.1	300	Series Filaments



### B-6 Double Contact Bayonet Base

Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
1004	40162	B-6	DC Bayonet	12.8	1.0	12	C-6	1.75/44.5	0.79/20.1	500
210	40454	B-6	DC Bayonet	6.5	1.78	15	C-6	1.75/44.5	0.79/20.1	100






23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### C-7 Candelabra Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Fila-ment	MOL in/mm	MOD in/mm	Avg. Life	Special Descrip-tion
	4C7/120V	40353	C-7	Candelabra Screw	115-125	4	C-7A	2.30/58.4	0.88/22.3	3000	
4C7/130V	40351	C-7	Candelabra Screw	130	4	C-7A	2.30/58.4	0.88/22.3	3000		
4C7/130V-B	44304	C-7	Candelabra Screw	130	4	C-7A	2.30/58.4	0.88/22.3	3000	Painted Blue	
4C7/130V-P	44308	C-7	Candelabra Screw	130	4	C-7A	2.30/58.4	0.88/22.3	3000	Painted Pink	
4C7/130V-W	44312	C-7	Candelabra Screw	130	4	C-7A	2.30/58.4	0.88/22.3	3000	Painted White	
7C7/120V	40874	C-7	Candelabra Screw	115-125	7	C-7A	2.30/58.4	0.88/22.3	3000		
7C7/130V	40875	C-7	Candelabra Screw	130	7	C-7A	2.30/58.4	0.88/22.3	3000		
7C7/130V-W	44318	C-7	Candelabra Screw	130	7	C-7A	2.30/58.4	0.88/22.3	3000	Painted White	
10C7/120V	40073	C-7	Candelabra Screw	120	10	C-7A	2.30/58.4	0.88/22.3	5000+		


### C-7 Double Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Filament	MOL in/mm	MOD in/mm	Avg. Life
	10C7DC/120V	40154	C-7	DC Bayonet	115-125	10	C-7A	2.13/54.1	0.88/22.3	5000+


### Festoon 8mm - SV7mm Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	DE3021	42216	Festoon 8mm	SV7mm	14	0.24	2.00	C-8	1.10/28.0	0.32/8.0	1000
DE3022	42308	Festoon 8mm	SV7mm	13	0.38	3.00	C-8	1.15/29.2	0.32/8.0	1000	

### Festoon 10mm - SV8.5mm Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Description
	6418	40675	Festoon 10mm	SV8.5mm	12	0.4	3.6	C-8	1.38/35.1	0.43/11.0	300	ECE Type - CSW
6411	40671	Festoon 10mm	SV8.5mm	12	0.83	8.0	C-8	1.61/40.9	0.43/11.0	200		
211-2/F	42312	Festoon 10mm	SV8.5mm	12.8	0.97	12.0	C-8	1.72/43.7	0.42/10.54	1000		
DE3423	42222	Festoon 10mm	SV8.5mm	13	0.39	4.0	C-8	1.46/37.1	0.43/11.0	150		
DE3175	42298	Festoon 10mm	SV8.5mm	13	0.77	9.55	C-8	1.23/31.3	0.40/10.0	400		
DE3425	42424	Festoon 10mm	SV8.5mm	13	0.77	9.55	C-8	1.46/37.1	0.43/11.0	400		

### Festoon 10mm - SV8.5mm Base - Xenon

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Description
	KO10XE/F		Festoon 10mm	SV8.5mm	13.5	0.37	4.0	C-8	1.73/44.0	0.40/10.0	4000	Xenon, Frosted
KO16XE/F		Festoon 10mm	SV8.5mm	13.5	0.74	9.55	C-8	1.73/44.0	0.40/10.0	3000	Xenon, Frosted	
KO20XE/F		Festoon 10mm	SV8.5mm	26	0.192	4.0	C-8	1.73/44.0	0.40/10.0	3000	Xenon, Frosted	
KO23XE/F		Festoon 10mm	SV8.5mm	26	0.385	9.55	C-8	1.73/44.0	0.40/10.0	3000	Xenon, Frosted	
KK14XE	50058	Festoon 10mm	SV8.5mm	13	0.62	12.0	C-8	1.22/31.0	0.40/10.0	500	Xenon	
KK10XE	50056	Festoon 10mm	SV8.5mm	13.5	0.37	4.0	C-8	1.22/31.0	0.40/10.0	5000	Xenon	
KN10XE	50076	Festoon 10mm	SV8.5mm	13.5	0.37	4.0	C-8	1.53/39.0	0.40/10.0	5000	Xenon	
KO10XE	50086	Festoon 10mm	SV8.5mm	13.5	0.37	4.0	C-8	1.73/44.0	0.40/10.0	5000	Xenon	
KO16XE	50090	Festoon 10mm	SV8.5mm	13.5	0.74	9.55	C-8	1.73/44.0	0.40/10.0	5000	Xenon	
KK20XE	50062	Festoon 10mm	SV8.5mm	26	0.192	4.0	C-8	1.22/31.0	0.40/10.0	5000	Xenon	
KL20XE	50072	Festoon 10mm	SV8.5mm	26	0.192	4.0	C-8	1.45/37.0	0.40/10.0	5000	Xenon	
KN20XE	50082	Festoon 10mm	SV8.5mm	26	0.192	4.0	C-8	1.53/39.0	0.40/10.0	5000	Xenon	
KO20XE	50092	Festoon 10mm	SV8.5mm	26	0.192	4.0	C-8	1.73/44.0	0.40/10.0	5000	Xenon	
KL23XE	50074	Festoon 10mm	SV8.5mm	26	0.385	9.55	C-8	1.45/37.0	0.40/10.0	3000	Xenon	
KO23XE	50094	Festoon 10mm	SV8.5mm	26	0.385	9.55	C-8	1.73/44.0	0.40/10.0	3000	Xenon	



23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679

www.eiko.com  
eiko@eiko.com

## MINIATURE

### G-3½ Miniature 2 Pin Base



Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
10	40152	G-3 1/2	Miniature 2 Pin	2.5	0.5	0.50	C-6	0.94/23.9	0.43/11.0	3000
12	40214	G-3 1/2	Miniature 2 Pin	6.3	0.15	0.35	C-6	0.94/23.9	0.43/11.0	5000
19	41070	G-3 1/2	Miniature 2 Pin	14.4	0.1	0.90	C-6	0.94/23.9	0.43/11.0	1000

### G-3½ Miniature Bayonet Base



Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
A-62	48000	G-3 1/2	BA-9S	6.75	1.5W	1.0	C-2R	0.94/23.9	0.43/11.0	
A-72	48002	G-3 1/2	BA-9S	13.5	4W	2.8	C-2R	0.94/23.9	0.43/11.0	4000
130	49671	G-3 1/2	BA-9S	6.3	0.15	0.32	C-2R	0.94/23.9	0.43/11.0	5000
219	49701	G-3 1/2	Miniature Bayonet	6.3	0.25	0.5	C-2V	0.94/23.9	0.43/11.0	5000
51	40756	G-3 1/2	Miniature Bayonet	7.5	0.22	1.00	C-2R	0.94/23.9	0.43/11.0	1000
363	40640	G-3 1/2	Miniature Bayonet	14	0.2	2.00	C-2V	0.94/23.9	0.43/11.0	250
53	40761	G-3 1/2	BA-9S	14.4	0.12	1.00	C-2V	0.94/23.9	0.43/11.0	1000
1445	40271	G-3 1/2	Miniature Bayonet	14.4	0.135	0.70	C-2V	0.94/23.9	0.43/11.0	2000
1450	49624	G-3 1/2	Miniature Bayonet	24	0.035	0.23	C-2F	0.94/23.9	0.43/11.0	3000
356	40636	G-3 1/2	Miniature Bayonet	28	0.17	3.50	C-2V	0.94/23.9	0.43/11.0	500
265	49707	G-3 1/2	Miniature Bayonet	28	0.08	0.75	C-2F	0.94/23.9	0.43/11.0	5000

### G-3½ Miniature Screw Base



Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
123	40237	G-3 1/2	Miniature Screw	1.25	0.3	0.10	S-2	0.94/23.9	0.43/11.0	10
131	40252	G-3 1/2	Miniature Screw	1.3	0.1	0.03	S-2	0.94/23.9	0.43/11.0	50
359	49787	G-3 1/2	Miniature Screw	1.35	0.06	0.02	S-2	0.94/23.9	0.43/11.0	50
233	49702	G-3 1/2	Miniature Screw	2.33	0.27	0.42	C-2R	0.94/23.9	0.43/11.0	10
245	49703	G-3 1/2	Miniature Screw	2.46	0.5	0.9	C-2R	0.94/23.9	0.43/11.0	15
14	40264	G-3 1/2	Miniature Screw	2.47	0.3	0.50	C-2R	0.94/23.9	0.43/11.0	15
365	49708	G-3 1/2	Miniature Screw	3.69	0.5	1.6	C-2R	0.94/23.9	0.43/11.0	15
13	40247	G-3 1/2	Miniature Screw	3.7	0.3	0.98	C-2R	0.94/23.9	0.43/11.0	15
50	40746	G-3 1/2	Miniature Screw	7.5	0.22	1.00	C-2R	0.94/23.9	0.43/11.0	1000
1449	40276	G-3 1/2	Miniature Screw	14	0.2	2.00	C-2V	0.94/23.9	0.43/11.0	250
52	40760	G-3 1/2	Miniature Screw	14.4	0.1	0.75	C-2V	0.94/23.9	0.43/11.0	1000
1447	49696	G-3 1/2	Miniature Screw	18	0.15	1.5	C-2V	0.94/23.9	0.43/11.0	250

### G-4½ Miniature 2 Pin Base



Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
15	40290	G-4 1/2	Miniature 2 Pin	7	0.4	2.0	C-6	1.06/26.9	0.59/15.0	500

### G-4½ Miniature Bayonet Base



Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
503	40752	G-4 1/2	Miniature Bayonet	5.1	0.15	0.6	C-2R	1.07/27.2	0.59/15.0	100	
455	40720	G-4 1/2	Miniature Bayonet	6.5	0.5	1.9	C-2R	1.07/27.2	0.59/15.0	500	Flasher
6253	40667	G-4 1/2	Miniature Bayonet	12	0.5	4.2	C-2V	1.07/27.2	0.59/15.0	200	
1895A	40419	G-4 1/2	Miniature Bayonet	14	0.27	-	C-2F	1.07/27.2	0.59/15.0	2000	Painted Amber
1895B	40719	G-4 1/2	Miniature Bayonet	14	0.27	-	C-2F	1.07/27.2	0.59/15.0	2000	Painted Blue
1895R	40725	G-4 1/2	Miniature Bayonet	14	0.27	-	C-2F	1.07/27.2	0.59/15.0	2000	Painted Red
293	40550	G-4 1/2	Miniature Bayonet	14	0.33	2.0	C-2F	1.07/27.2	0.59/15.0	5000	
1895	40416	G-4 1/2	Miniature Bayonet	14	0.27	2.0	C-2F	1.07/27.2	0.59/15.0	2000	

Continued on next page ►►




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### G-4½ Miniature Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>407</b>	40698	G-4 1/2	Miniature Screw	4.9	0.3	1.20	C-2R	1.07/27.2	0.59/15.0	50	Flasher Lamp
<b>27</b>	40539	G-4 1/2	Miniature Screw	4.9	0.3	1.4	C-2R	1.07/27.2	0.59/15.0	30		
<b>425</b>	40702	G-4 1/2	Miniature Screw	5	0.5	2.30	C-2R	1.07/27.2	0.59/15.0	15		
<b>502</b>	40750	G-4 1/2	Miniature Screw	5.1	0.15	0.60	C-2R	1.07/27.2	0.59/15.0	100		
<b>31</b>	40574	G-4 1/2	Miniature Screw	6.15	0.3	2.00	C-2R	1.07/27.2	0.59/15.0	15		
<b>605</b>	40826	G-4 1/2	Miniature Screw	6.15	0.5	3.40	C-2R	1.07/27.2	0.59/15.0	15		
<b>428</b>	40704	G-4 1/2	Miniature Screw	12.5	0.25	2.40	C-2V	1.07/27.2	0.59/15.0	250		
<b>258</b>	49706	G-4 1/2	Miniature Screw	14	0.27	-	C-2R	1.07/27.2	0.59/15.0	500		
<b>432</b>	49726	G-4 1/2	Miniature Screw	18	0.25	-	C-2V	1.07/27.2	0.59/15.0	250		


### G-5 Miniature Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>1464</b>	49697	G-5	Miniature Bayonet	22	.25	3.8	C-6	1.19/30.2	.62/15.8	250


### G-6 Candelabra Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>67K</b>	49711	G-6	Candelabra Screw	13.5	0.59	4	C-2R	1.38/35.1	0.75/19.1	5000
<b>509K</b>	40754	G-6	Candelabra Screw	24	0.18	2.8	C-2F	1.38/35.1	0.75/19.1	1000	
<b>1224K</b>	49692	G-6	Candelabra Screw	32	0.16	4	C-2F	1.38/35.1	0.75/19.1	200	

### G-6 Single Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>81</b>	40958	G-6	SC Bayonet	6.5	1.02	6.0	C-6	1.44/36.6	0.75/19.1	500	
<b>63</b>	40830	G-6	SC Bayonet	7	0.63	3.0	C-6	1.44/36.6	0.75/19.1	1000		
<b>98</b>	41048	G-6	SC Bayonet	13	0.62	6.0	C-6	1.44/36.6	0.75/19.1	800		
<b>1155</b>	40188	G-6	SC Bayonet	13.5	0.59	4.0	C-6/C-6	1.44/36.6	0.75/19.1	5000	Series Filaments, Rated 5000 hrs at 14V	
<b>97A</b>	41046	G-6	SC Bayonet	13.5	0.69	-	C-6	1.44/36.6	0.75/19.1	5000	Painted Amber, Rated 5000 hrs at 14V	
<b>631</b>	40832	G-6	SC Bayonet	14	0.63	6.0	C-6/C-6	1.44/36.6	0.75/19.1	1000	Series Filaments	
<b>1251</b>	40242	G-6	SC Bayonet	28	0.23	3.0	C-6/C-6	1.44/36.6	0.75/19.1	2000	Series Filaments	
<b>303</b>	40562	G-6	SC Bayonet	28	0.3	6.0	CC-6	1.44/36.6	0.75/19.1	500		
<b>623</b>	40828	G-6	SC Bayonet	28	0.37	6.0	2C-6	1.44/36.6	0.75/19.1	1000	Series Filaments	

### G-6 Double Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>82</b>	40964	G-6	DC Bayonet	6.5	1.02	6.0	C-6	1.44/36.6	0.75/19.1	500	
<b>64</b>	40835	G-6	DC Bayonet	7	0.63	3.0	C-6	1.44/36.6	0.75/19.1	1000		
<b>90</b>	41005	G-6	DC Bayonet	13	0.58	6.0	C-6	1.44/36.6	0.75/19.1	750		
<b>96</b>	41041	G-6	DC Bayonet	13.5	0.69	4	C-2V	1.44/36.6	0.75/19.1	5000		
<b>1178</b>	49091	G-6	DC Bayonet	13.5	0.69	4	C-2V	1.44/36.6	0.75/19.1	5000		
<b>1252</b>	40244	G-6	DC Bayonet	28	0.23	3.0	C-6/C-6	1.44/36.6	0.75/19.1	2000	Series Filaments	
<b>304</b>	49103	G-6	DC Bayonet	28	0.3	6	C-2F	1.44/36.6	0.75/19.1	500		
<b>624</b>	40829	G-6	DC Bayonet	28	0.37	6.0	2C-6	1.44/36.6	0.75/19.1	1000	Series Filaments	
<b>1224</b>	40234	G-6	DC Bayonet	32	0.16	3.8	C-2F	1.44/36.6	0.75/19.1	200		



23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679

www.eiko.com  
eiko@eiko.com

## MINIATURE

### R-12 Single Contact Bayonet Base



Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
1383	40258	R-12	SC Bayonet	13	1.5	-	CC-8	2.63/66.8	1.55/39.4	300	Top frosted, Bottom reflectorized
1383TF	40259	R-12	SC Bayonet	13	1.5	-	CC-8	2.63/66.8	1.55/39.4	300	Top frosted, Bottom reflectorized, Silicon Coated
1385	40262	R-12	SC Bayonet	28	0.72	-	CC-8	2.63/66.8	1.55/39.4	300	Top frosted, Bottom reflectorized

### RP-11 Single Contact Bayonet Base



Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
1133	40174	RP-11	SC Bayonet	6.2	3.91	32	C-6	2.25/7.2	1.42/36.1	200
1143	49635	RP-11	SC Bayonet	12.5	1.98	32	C-2R	2.25/7.2	1.42/36.1	400
1143IF	49636	RP-11	SC Bayonet	12.5	1.98	-	C-2R	2.25/7.2	1.42/36.1	400
1195	40210	RP-11	SC Bayonet	12.5	3.0	50	C-2V	2.25/7.2	1.42/36.1	300

### RP-11 Double Contact Bayonet Base



Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
1144	49637	RP-11	DC Bayonet	12.5	1.98	32	C-2R	2.25/57.2	1.42/36.1	400
1196	40213	RP-11	DC Bayonet	12.5	3.0	50	C-2V	2.25/57.2	1.42/36.1	300
1062	49618	RP-11	DC Bayonet	40	0.92	50	C-2V	2.25/57.2	1.42/36.1	100

### S-6 Candelabra Screw Base



Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
6S6/6V	40798	S-6	Candelabra Screw	6	6	4.3	C-6	1.88/47.8	0.75/19.1	1500
6S6/12V	40784	S-6	Candelabra Screw	12	6	3.8	C-6	1.88/47.8	0.75/19.1	1500
6S6/18V	49717	S-6	Candelabra Screw	18	6	4.0	C-6	1.88/47.8	0.75/19.1	1500
6S6/24V	40792	S-6	Candelabra Screw	24	6	4.2	C-6	1.88/47.8	0.75/19.1	1500
6S6/30V	40794	S-6	Candelabra Screw	30	6	4.1	C-6	1.88/47.8	0.75/19.1	1500
6S6/48V	40796	S-6	Candelabra Screw	48	6	3.7	C-6	1.88/47.8	0.75/19.1	1500
6S6/60V	40800	S-6	Candelabra Screw	60	6	3.4	C-7A	1.88/47.8	0.75/19.1	1500
3S6/5-120V	40552	S-6	Candelabra Screw	120	3	0.9	C-7A	1.88/47.8	0.75/19.1	3000
6S6/120V	40786	S-6	Candelabra Screw	120	6	3.1	C-7A	1.88/47.8	0.75/19.1	1500
3S6/5-130V	40554	S-6	Candelabra Screw	130	3	0.9	C-7A	1.88/47.8	0.75/19.1	1500
6S6/130V	40788	S-6	Candelabra Screw	130	6	3.0	C-7A	1.88/47.8	0.75/19.1	1500
6S6/145V	40789	S-6	Candelabra Screw	145	6	1.4	C-7A	1.88/47.8	0.75/19.1	1500
6S6/155V	40790	S-6	Candelabra Screw	155	6	2.6	C-7A	1.88/47.8	0.75/19.1	1500
6S6/230V	40791	S-6	Candelabra Screw	230	6	0.9	C-7A	1.88/47.8	0.75/19.1	1500
10S6/230V	42446	S-6	Candelabra Screw	230	10	4.8	C-7A	1.88/47.8	0.75/19.1	1500

### S-6 Double Contact Bayonet Base



Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
6S6DC/6V	40814	S-6	DC Bayonet	6	6	4.3	C-6	1.82/46.2	0.75/19.1	1500
6S6DC/12V	40802	S-6	DC Bayonet	12	6	3.8	C-6	1.82/46.2	0.75/19.1	1500
6S6DC/24V	40808	S-6	DC Bayonet	24	6	4.2	C-6	1.82/46.2	0.75/19.1	1500
6S6DC/30V	40810	S-6	DC Bayonet	30	6	4.1	C-6	1.82/46.2	0.75/19.1	1500
6S6DC/32V	40811	S-6	DC Bayonet	32	6	4.0	C-6	1.82/46.2	0.75/19.1	1500
6S6DC/48V	40812	S-6	DC Bayonet	48	6	3.7	C-6	1.82/46.2	0.75/19.1	1500
6S6DC/60V	40816	S-6	DC Bayonet	60	6	3.4	C-7A	1.82/46.2	0.75/19.1	1500
3S6/5DC-120V	40556	S-6	DC Bayonet	120	3	0.9	C-7A	1.82/46.2	0.75/19.1	3000

Continued on next page ►►



23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679

www.eiko.com  
eiko@eiko.com

## MINIATURE

### S-6 Double Contact Bayonet Base (Continued)

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>356/5DC-130V*</b>	40558		S-6	DC Bayonet	130	3	0.9	C-7A	1.82/46.2	0.75/19.1
<b>656DC/130V*</b>	40806		S-6	DC Bayonet	130	6	3.0	C-7A	1.82/46.2	0.75/19.1	1500*
<b>656DC/145V</b>	40807		S-6	DC Bayonet	145	6	1.4	C-7A	1.82/46.2	0.75/19.1	1500
<b>1056DC/250V</b>	40149		S-6	DC Bayonet	250	10	4.8	C-7A	1.82/46.2	0.75/19.1	1500

\* 130 volt lamps are rated at **3,750** hours when operated at 120 volts.

### S-8 Single Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>1651</b>	40316		S-8	SC Bayonet	5	0.6	3	C-6	2.00/50.8	1.04/26.4	20
<b>1129</b>	40170		S-8	SC Bayonet	6.4	2.63	21	C-6	2.00/50.8	1.04/26.4	200	
<b>1619</b>	49626		S-8	SC Bayonet	6.7	1.9	15	C-6	2.00/50.8	1.04/26.4	500	
<b>87</b>	40986		S-8	SC Bayonet	6.8	1.91	15	C-6	2.00/50.8	1.04/26.4	300	
<b>93</b>	41033		S-8	SC Bayonet	12.8	1.04	15	C-6	2.00/50.8	1.04/26.4	700	
<b>1295</b>	40246		S-8	SC Bayonet	12.5	3.0	50	C-6	2.00/50.8	1.04/26.4	200	
<b>1295NA</b>	42172		S-8	SC Bayonet	12.5	3.0	37	C-6	2.00/50.8	1.04/26.4	300	Hi-Temp Amber Paint
<b>1093</b>	49684		S-8	SC Bayonet	12.8	1.19	15	C-6	2.00/50.8	1.04/26.4	1000	
<b>1141</b>	40176		S-8	SC Bayonet	12.8	1.6	21	C-6	2.00/50.8	1.04/26.4	1500	
<b>1141LL</b>	42514		S-8	SC Bayonet	12.8	1.6	21	C-6	2.00/50.8	1.04/26.4	2000	Long Life, Krypton Filled
<b>1141IF</b>	40115		S-8	SC Bayonet	12.8	1.6	-	C-6	2.00/50.8	1.04/26.4	1000	Inside Frosted
<b>1073</b>	40165		S-8	SC Bayonet	12.8	1.8	32	C-6	2.00/50.8	1.04/26.4	200	
<b>1156</b>	40190		S-8	SC Bayonet	12.8	2.1	32	C-6	2.00/50.8	1.04/26.4	1200	
<b>1156LL</b>	42516		S-8	SC Bayonet	12.8	2.1	32	C-6	2.00/50.8	1.04/26.4	2400	Long Life, Krypton Filled
<b>1156A</b>	44030		S-8	SC Bayonet	12.8	2.1	-	C-6	2.00/50.8	1.04/26.4	1200	Painted Amber
<b>1156B</b>	00354		S-8	SC Bayonet	12.8	2.1	-	C-6	2.00/50.8	1.04/26.4	1200	Hi-Temp Blue Paint
<b>1156G</b>	00352		S-8	SC Bayonet	12.8	2.1	-	C-6	2.00/50.8	1.04/26.4	1200	Hi-Temp Green Paint
<b>1156P</b>	00355		S-8	SC Bayonet	12.8	2.1	-	C-6	2.00/50.8	1.04/26.4	1200	Hi-Temp Purple Paint
<b>1156R</b>	00351		S-8	SC Bayonet	12.8	2.1	-	C-6	2.00/50.8	1.04/26.4	1200	Hi-Temp Red Paint
<b>1156Y</b>	00353		S-8	SC Bayonet	12.8	2.1	-	C-6	2.00/50.8	1.04/26.4	1200	Hi-Temp Yellow Paint
<b>1156NA</b>	40193		S-8	SC Bayonet	12.8	2.1	24	C-6	2.00/50.8	1.04/26.4	1200	Hi-Temp Amber Paint
<b>2396</b>	40504		S-8	SC Bayonet	12.8	2.23	40	C-6	2.00/50.8	1.04/26.4	400	
<b>199</b>	40445		S-8	SC Bayonet	12.8	2.25	32	C-6	2.00/50.8	1.04/26.4	1200	
<b>7506</b>	42241		S-8	SC Bayonet	13.5	1.86	36.6	C-6	2.00/50.8	1.04/26.4	350	ECE Type - P21W
<b>7511</b>	00233		S-8	SC Bayonet	28	1.00	35	C-6	2.00/50.8	1.04/26.4	350	ECE Type - P21W/24V
<b>P21-W</b>	44009		S-8	SC Bayonet	13.5	1.86	36.6	C-6	2.06/52.5	1.05/26.5	350	E-Mark
<b>P25-1</b>	40082		S-8	SC Bayonet	13.5	1.86	36.6	C-6	2.06/52.5	1.05/26.5	350	E-Mark
<b>1591</b>	40305		S-8	SC Bayonet	28	0.61	15	C-6	2.00/50.8	1.04/26.4	1000	
<b>1691</b>	40324		S-8	SC Bayonet	28	0.61	15	2C-6	2.00/50.8	1.04/26.4	1000	Series Filaments
<b>2232</b>	42384		S-8	SC Bayonet	28	0.643	18	CC-8	2.00/50.8	1.04/26.4	2000	Spiral lead
<b>307</b>	40568		S-8	SC Bayonet	28	0.67	21	C-6	2.00/50.8	1.04/26.4	300	
<b>1203</b>	40232		S-8	SC Bayonet	28	0.71	21	C-6	2.00/50.8	1.04/26.4	400	
<b>2233</b>	42386		S-8	SC Bayonet	28	0.766	21	CC-8	2.00/50.8	1.04/26.4	2000	Spiral lead
<b>315</b>	40580		S-8	SC Bayonet	28	0.9	32	CC-6	2.00/50.8	1.04/26.4	300	
<b>1683</b>	40322		S-8	SC Bayonet	28	1.02	32	2C-6	2.00/50.8	1.04/26.4	500	Series Filaments

### S-8 BAZ15D Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>7225</b>	42237		S-8	BAZ15D	13.5	1.852/0.0370	35/1.2	C-6	2.0/50.8	1.04/26.4




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### S-8 Double Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	1130	40172	S-8	DC Bayonet	6.4	2.63	21	C-6	2.00/50.8	1.04/26.4	200	
	1158	40202	S-8	DC Bayonet	6.4/7	2.63/0.75	21/3	C-6/C-6	2.00/50.8	1.04/26.4	200 / 1000	
	1493	40701	S-8	DC Bayonet	6.4	2.75	23	C-6	2.00/50.8	1.04/26.4	100	
	88	40992	S-8	DC Bayonet	6.8	1.91	15	C-6	2.00/50.8	1.04/26.4	300	
	94	41037	S-8	DC Bayonet	12.8	1.04	15	C-6	2.00/50.8	1.04/26.4	700	
	1152	40184	S-8	DC Bayonet	12.8	1.34	21	C-6	2.00/50.8	1.04/26.4	500	
	1176	40204	S-8	DC Bayonet	12.8/14	1.34/0.59	21/6	C-6/C-6	2.00/50.8	1.04/26.4	300 / 1500	
	1076	40167	S-8	DC Bayonet	12.8	1.8	32	C-6	2.00/50.8	1.04/26.4	200	
	1156DC	44334	S-8	DC Bayonet	12.8	2.1	32	C-6	2.00/50.8	1.04/26.4	1200	
	306	40566	S-8	DC Bayonet	28	0.51	15	C-6	2.00/50.8	1.04/26.4	300	
	1692	40326	S-8	DC Bayonet	28	0.61	15	2C-6	2.00/50.8	1.04/26.4	1000	Series Filaments
	308	40570	S-8	DC Bayonet	28	0.67	21	C-6	2.00/50.8	1.04/26.4	300	
	1204	49080	S-8	DC Bayonet	28	0.71	21	C-6	2.00/50.8	1.04/26.4	400	
	1638	40315	S-8	DC Bayonet	28	1.02	32	2C-6	2.00/50.8	1.04/26.4	500	
	1228	49693	S-8	DC Bayonet	32	0.45	15	C-6	2.00/50.8	1.04/26.4	150	
	895	41004	S-8	DC Bayonet	40	0.53	14	CC-6	2.00/50.8	1.04/26.4	3800	
	7537	00234	S-8	DC Bayonet	28/28	1.00/0.36	35/3	C-6/C-6	2.00/50.8	1.04/26.4	300/2000	

### S-8 Double Contact Index Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	1154	40186	S-8	DC Index Bayonet	6.4/7	2.63/0.75	21/3	C-6/C-6	2.00/50.8	1.04/26.4	200 / 1000	
	1016	40166	S-8	DC Index Bayonet	12.8/14	1.34/0.59	21/6	C-6/C-6	2.00/50.8	1.04/26.4	300 / 1000	
	1034	40161	S-8	DC Index Bayonet	12.8/14	1.8/0.59	32/3	C-6/C-6	2.00/50.8	1.04/26.4	200 / 5000	
	2057	40448	S-8	DC Index Bayonet	12.8/14	2.1/0.48	32/2	C-6/C-6	2.00/50.8	1.04/26.4	1200 / 5000	
	2057LL	42522	S-8	DC Index Bayonet	12.8/14	2.1/0.48	32/2	C-6/C-6	2.00/50.8	1.04/26.4	2400 / 10000	Long Life
	2057A	42262	S-8	DC Index Bayonet	12.8/14	2.1/0.48	-	C-6/C-6	2.00/50.8	1.04/26.4	1200 / 5000	Painted Amber
	2057NA	40455	S-8	DC Index Bayonet	12.8/14	2.1/0.48	24/1.5	C-6/C-6	2.00/50.8	1.04/26.4	1200 / 5000	Hi-Temp Amber Paint
	2057NALL	42524	S-8	DC Index Bayonet	12.8/14	2.1/0.48	24/1.5	C-6/C-6	2.00/50.8	1.04/26.4	2400 / 10000	Hi-Temp Amber Paint, Long Life Krypton Filled
	1157	40194	S-8	DC Index Bayonet	12.8/14	2.1/0.59	32/3	C-6/C-6	2.00/50.8	1.04/26.4	1200 / 5000	
	1157LL	42518	S-8	DC Index Bayonet	12.8/14	2.1/0.59	32/3	C-6/C-6	2.00/50.8	1.04/26.4	2400 / 10000	Long Life Krypton Filled
	1157A	40197	S-8	DC Index Bayonet	12.8/14	2.1/0.59	-	C-6/C-6	2.00/50.8	1.04/26.4	1200 / 5000	Painted Amber Glass
	1157NA	40199	S-8	DC Index Bayonet	12.8/14	2.1/0.59	24/2.2	C-6/C-6	2.00/50.8	1.04/26.4	1200 / 5000	Hi-Temp Amber Paint
	2397	42229	S-8	DC Index Bayonet	12.8/14	2.23/0.48	40/2	C-6/C-6	2.00/50.8	1.04/26.4	400 / 2000	
	2357	40498	S-8	DC Index Bayonet	12.8/14	2.23/0.59	40/3	C-6/C-6	2.00/50.8	1.04/26.4	400 / 5000	
	2357LL	42526	S-8	DC Index Bayonet	12.8/14	2.23/0.59	40/3	C-6/C-6	2.00/50.8	1.04/26.4	800 / 10000	Long Life Krypton Filled
	2357A	42304	S-8	DC Index Bayonet	12.8/14	2.23/0.59	-	C-6/C-6	2.00/50.8	1.04/26.4	400 / 5000	Painted Amber Glass
	2357NA	40501	S-8	DC Index Bayonet	12.8/14	2.23/0.59	30/2.2	C-6/C-6	2.00/50.8	1.04/26.4	400 / 5000	Hi-Temp Amber Paint
	198	40443	S-8	DC Index Bayonet	12.8/14	2.25/0.59	32/3	C-6/C-6	2.00/50.8	1.04/26.4	1200 / 5000	
	198LL	42508	S-8	DC Index Bayonet	12.8/14	2.25/0.59	32/3	C-6/C-6	2.00/50.8	1.04/26.4	2400 / 10000	Long Life Krypton Filled
	7528	42245	S-8	DC Index Bayonet	13.5/13.5	1.86/0.44	35/2.8	C-6/C-6	2.00/50.8	1.04/26.4	300/2000	ECE Type - P21/5W
	P21/5W	44011	S-8	DC Index Bayonet	13.5/13.5	1.86/0.44	35/2.8	C-6/C-6	2.06/52.5	1.05/26.5	300/2000	E Mark
	P25-2	40083	S-8	DC Index Bayonet	13.5/13.5	1.86/0.44	35/2.8	C-6/C-6	2.06/52.5	1.05/26.5	300/2000	E-Mark
	1662	42382	S-8	DC Index Bayonet	28/28	0.93/0.34	32/6	CC-6/C-6	2.00/50.8	1.04/26.4	400 / 1000	Filament connections reversed from normal DC Index

### S-8 Single Contact Prefocus Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Replaces
	55A/S8	41702	S-8	SC Prefocus	12	0.55	5.57	C-8S	2.09/53.1	1.04/26.4	500	CM2374X
	77A/S8	41704	S-8	SC Prefocus	12	0.77	9.55	C-8S	2.09/53.1	1.04/26.4	500	CM2033X




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### S-8 Double Contact Prefocus Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>1096</b>	40401	S-8	DC Prefocus	6	4.5	30	C-2R	2.00/50.8	1.04/26.4	500	
<b>1096X</b>	40403	S-8	DC Prefocus	6	4.5	30	C-2R	2.00/50.8	1.04/26.4	500		Silver Contacts
<b>1468X</b>	40405	S-8	DC Prefocus	6	4.5	30	C-2R	2.00/50.8	1.04/26.4	500		Silver Contacts
<b>1460</b>	40279	S-8	DC Prefocus	6.5	2.75	23	C-6	2.00/50.8	1.04/26.4	100		
<b>1460X</b>	40281	S-8	DC Prefocus	6.5	2.75	23	C-6	2.00/50.8	1.04/26.4	100		Silver Contacts
<b>1630</b>	40311	S-8	DC Prefocus	6.5	2.75	23	C-6	2.00/50.8	1.04/26.4	100		
<b>1631X</b>	40312	S-8	DC Prefocus	6.5	2.75	23	C-6	2.00/50.8	1.04/26.4	100		Silver Contacts
<b>1649</b>	40705	S-8	DC Prefocus	6.5	2.75	23	FC-6Z	2.00/50.8	1.04/26.4	100		
<b>1634</b>	40313	S-8	DC Prefocus	20	1.0	24	CC-6	2.00/50.8	1.04/26.4	200		


### S-8 Plastic Wedge Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>3057</b>	40600	S-8	Plastic Wedge	12.8/14	2.1/0.48	32/2	C-6/C-6	2.09/53.1	1.04/26.4	1200 / 5000	
<b>3057A</b>	42621	S-8	Plastic Wedge	12.8/14	2.1/0.48	-	C-6/C-6	2.09/53.1	1.04/26.4	1200/5000		Painted Amber
<b>3057K</b>	42600	S-8	Plastic Wedge	12.8/14	2.1/0.48	32/2	C-6/C-6	2.09/53.1	1.04/26.4	2000 / 10000		Long Life Krypton Filled
<b>3057NA</b>	40603	S-8	Plastic Wedge	12.8/14	2.1/0.48	24/1.5	C-6/C-6	2.09/53.1	1.04/26.4	1200 / 5000		Hi-Temp Amber Paint
<b>3155</b>	42288	S-8	Plastic Wedge	12.8	1.6	21	C-6	2.09/53.1	1.04/26.4	1500		
<b>3155K</b>	49718	S-8	Plastic Wedge	12.8	1.44	21	C-6	2.09/53.1	1.04/26.4	2000		Long Life Krypton Filled
<b>3156</b>	42292	S-8	Plastic Wedge	12.8	2.1	32	C-6	2.09/53.1	1.04/26.4	1200		
<b>3156A</b>	49035	S-8	Plastic Wedge	12.8	2.1	-	C-6	2.09/53.1	1.04/26.4	1200		Painted Amber
<b>3156K</b>	42603	S-8	Plastic Wedge	12.8	2.1	32	C-6	2.09/53.1	1.04/26.4	2000		Long Life Krypton Filled
<b>3157</b>	40610	S-8	Plastic Wedge	12.8/14	2.1/0.59	32/3	C-6/C-6	2.09/53.1	1.04/26.4	1200 / 5000		
<b>3157A</b>	42624	S-8	Plastic Wedge	12.8/14	2.1/0.59	24/2.2	C-6/C-6	2.09/53.1	1.04/26.4	1200/5000		Painted Amber
<b>3157K</b>	42606	S-8	Plastic Wedge	12.8/14	2.1/0.59	32/3	C-6/C-6	2.09/53.1	1.04/26.4	2000 / 10000		Long Life Krypton Filled
<b>3157NA</b>	40613	S-8	Plastic Wedge	12.8/14	2.1/0.59	24/2.2	C-6/C-6	2.09/53.1	1.04/26.4	1200 / 5000		Hi-Temp Amber Paint
<b>3357</b>	42189	S-8	Plastic Wedge	12.8/14	2.23/0.59	40/3	C-6/C-6	2.09/53.1	1.04/26.4	400 / 5000		
<b>3357A</b>	49037	S-8	Plastic Wedge	12.8/14	2.23/0.59	30/2.2	C-6/C-6	2.09/53.1	1.04/26.4	400 / 5000		Painted Amber
<b>3357NA</b>	42195	S-8	Plastic Wedge	12.8/14	2.23/0.59	30/2.2	C-6/C-6	2.09/53.1	1.04/26.4	400 / 5000		Hi-Temp Amber Paint
<b>3457/3357</b>	42192	S-8	Plastic Wedge	12.8/14	2.23/0.59	40/3	C-6/C-6	2.09/53.1	1.04/26.4	400 / 5000		
<b>3457A</b>	42597	S-8	Plastic Wedge	12.8/14	2.23/0.59	30/2.2	C-6/C-6	2.09/53.1	1.04/26.4	400 / 5000		Painted Amber
<b>3457/3357K</b>	42609	S-8	Plastic Wedge	12.8/14	2.23/0.59	40/3	C-6/C-6	2.09/53.1	1.04/26.4	800 / 10000		Long Life
<b>3457/3357NA</b>	42198	S-8	Plastic Wedge	12.8/14	2.23/0.59	30/2.2	C-6/C-6	2.09/53.1	1.04/26.4	400 / 5000		Hi-Temp Amber Paint
<b>3757NAK</b>	00183	S-8	Plastic Wedge	12.8/14	2.1/0.59	24/2.2	C-6/C-6	2.09/53.1	1.04/26.4	2000 / 10000		Long Life Krypton Filled, Hi-Temp Amber Paint
<b>4057K</b>	05390	S-8	Plastic Wedge	12.8/14	2.1/0.48	32/2	C-6/C-6	2.09/53.1	1.04/26.4	4000/10000		Long Life Krypton Filled
<b>4114K</b>		S-8	Plastic Wedge	14.4/14.4	2.23/0.59A	32/3	C-6/C-6	2.09/53.1	1.04/26.4	5000/10000		
<b>4157K</b>	81143	S-8	Plastic Wedge	12.8/14	2.23/0.59	32/3	C-6/C-6	2.09/53.1	1.04/26.4	4000 / 10000		Long Life Krypton Filled
<b>4157NAK</b>	81136	S-8	Plastic Wedge	12.8/14	2.23/0.59	24/2.2	C-6/C-6	2.09/53.1	1.04/26.4	5000 / 10000		Long Life Krypton Filled, Hi-Temp Amber Paint

### S-8 Wire Terminal Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>2058U</b>	40451	S-8	Wire Terminal	12.8/14	2.1/0.48	32/2	C-6/C-6	1.81/46.0	1.04/26.4	1200 / 5000

### S-11 Single Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>311</b>	40576	S-11	SC Bayonet	28	1.29	50	CC-2V	2.38/60.5	1.35/34.3	300




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### T-3/4 Wire Terminal Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
		<b>2</b>	40446	T-3/4	Wire Terminal	5	0.021	0.03	C-2R	0.20/5.1	0.09/2.3
	<b>6833</b>	40864	T-3/4	Wire Terminal	5	0.06	0.05	C-2R	0.20/5.1	0.09/2.3	25000


### T-1 Wire Terminal Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
		<b>6022</b>	40824	T-1	Wire Terminal	5	0.02	0.03	C-2R	0.25/6.4	0.13/3.2
	<b>680</b>	40852	T-1	Wire Terminal	5	0.06	0.03	C-2R	0.25/6.4	0.13/3.2	60000
	<b>683</b>	40856	T-1	Wire Terminal	5	0.06	0.05	C-2R	0.25/6.4	0.13/3.2	25000
	<b>715</b>	40884	T-1	Wire Terminal	5	0.115	0.15	C-2R	0.25/6.4	0.13/3.2	40000
	<b>7219</b>	42390	T-1	Wire Terminal	12	0.06	0.15	C-2F	0.25/6.4	0.13/3.2	10000
	<b>8111</b>	40960	T-1	Wire Terminal	14	0.065	0.15	C-2F	0.25/6.4	0.13/3.2	10000
	<b>6838</b>	40866	T-1	Wire Terminal	28	0.024	0.15	CC-2F	0.25/6.4	0.13/3.2	16000


### T-1 Bi-Pin Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
		<b>42005</b>	42005	T-1	Bi-Pin .050 (std)	1.35	0.32	0.17	C-2R	0.38/9.7	0.13/3.2
	<b>42006</b>	42006	T-1	Bi-Pin .050 (std)	2.7	0.32	0.70	C-2R	0.38/9.7	0.13/3.2	5
	<b>7683</b>	40944	T-1	Bi-Pin .050 (std)	5	0.06	0.05	C-2R	0.38/9.7	0.13/3.2	25000
	<b>7714</b>	40946	T-1	Bi-Pin .050 (std)	5	0.075	0.09	C-2R	0.38/9.7	0.13/3.2	25000
	<b>7715</b>	40948	T-1	Bi-Pin .050 (std)	5	0.115	0.15	C-2R	0.38/9.7	0.13/3.2	40000
	<b>7839</b>	40950	T-1	Bi-Pin .050 (std)	28	0.024	0.15	CC-2F	0.38/9.7	0.13/3.2	40000


### T-1 Sub-Midget Flange Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
		<b>685</b>	40872	T-1	Sub-Midget Flanged	5	0.06	0.05	C-2R	0.38/9.7	0.13/3.2
	<b>6839</b>	40868	T-1	Sub-Midget Flanged	28	0.024	0.15	CC-2F	0.38/9.7	0.13/3.2	16000


### T-1 1/4 Wire Terminal Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
		<b>2114</b>	40464	T-1 1/4	Wire Terminal	6	0.06	0.13	C-2R	0.46/11.7	0.17/4.3
	<b>8610</b>	40976	T-1 1/4	Wire Terminal	6.3	0.2	0.55	C-2R	0.46/11.7	0.17/4.3	5000
	<b>8640</b>	40982	T-1 1/4	Wire Terminal	14	0.08	0.50	C-2F	0.46/11.7	0.17/4.3	1000
	<b>8627</b>	40978	T-1 1/4	Wire Terminal	28	0.04	0.32	C-2F	0.46/11.7	0.17/4.3	1000

### T-1 1/4 Bi-Pin Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
		<b>7646</b>	49713	T-1 1/4	Bi-Pin .100	14	0.08	0.5	C-2R	0.60/15.2	0.17/4.3
	<b>7632</b>	40938	T-1 1/4	Bi-Pin .100	28	0.04	0.32	C-2F	0.60/15.2	0.17/4.3	1000

### T-1 1/2 MF Series

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
		<b>2721MF</b>		T-1 1/2	MF Series	12	0.1	0.48	C-2V	0.925/23.5	0.20/5.1




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### T-1½ Sub-Miniature Wedge Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>E79</b>	49456		T-1 1/2	W2x4.6d Sub-Min Wedge	6	0.2	0.60	C-2R	0.80/20.3	0.20/5.1
<b>E84</b>	49457		T-1 1/2	W2x4.6d Sub-Min Wedge	6.3	0.04	0.03	C-2R	0.80/20.3	0.20/5.1	20000
<b>E86</b>	49459		T-1 1/2	W2x4.6d Sub-Min Wedge	6.3	0.2	0.40	C-2F	0.80/20.3	0.20/5.1	20000
<b>2721</b>	42231		T-1 1/2	W2x4.6d Sub-Min Wedge	12	0.1	0.48	C-2V	0.80/20.3	0.20/5.1	1000
<b>E37</b>	49453		T-1 1/2	W2x4.6d Sub-Min Wedge	14	0.09	0.50	C-2F	0.80/20.3	0.20/5.1	2500
<b>E74</b>	49455		T-1 1/2	W2x4.6d Sub-Min Wedge	14	0.1	0.70	C-2F	0.80/20.3	0.20/5.1	1000
<b>E73</b>	49454		T-1 1/2	W2x4.6d Sub-Min Wedge	14	0.08	0.30	C-2F	0.80/20.3	0.20/5.1	15000
<b>E85</b>	49458		T-1 1/2	W2x4.6d Sub-Min Wedge	28	0.04	0.30	C-2F	0.80/20.3	0.20/5.1	7000
<b>E17</b>	49452		T-1 1/2	W2x4.6d Sub-Min Wedge	28	0.065	0.65	C-2F	0.80/20.3	0.20/5.1	5000


### T-1¾ Wire Terminal Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>2200</b>	40488		T-1 3/4	Wire Terminal	5	0.06	0.05	C-2R	0.52/13.2	0.23/5.9
<b>2181</b>	49106		T-1 3/4	Wire Terminal	6.3	0.2	0.4	C-2F	0.52/13.2	0.23/5.9	20000
<b>2112</b>	49700		T-1 3/4	Wire Terminal	6.3	0.2	0.55	C-2F	0.52/13.2	0.23/5.9	5000
<b>1869</b>	49698		T-1 3/4	Wire Terminal	10	0.014	-	C-2F	0.52/13.2	0.23/5.9	50000
<b>2174</b>	40470		T-1 3/4	Wire Terminal	12	0.04	0.10	C-2F	0.52/13.2	0.23/5.9	10000
<b>2182</b>	40478		T-1 3/4	Wire Terminal	14	0.08	0.30	C-2F	0.52/13.2	0.23/5.9	40000
<b>2162</b>	40468		T-1 3/4	Wire Terminal	14	0.1	0.50	C-2F	0.52/13.2	0.23/5.9	10000
<b>2176</b>	40472		T-1 3/4	Wire Terminal	24	0.05	0.50	C-2F	0.52/13.2	0.23/5.9	1000
<b>2187</b>	40484		T-1 3/4	Wire Terminal	28	0.04	0.30	C-2F	0.52/13.2	0.23/5.9	10000


### T-1¾ Sub-Miniature Wedge Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>56</b>	44326		T-1 3/4	W2.1x4.9d Sub-Min Wedge	5	0.115	0.15	C-2R	0.80/20.3	0.23/5.9
<b>79</b>	44328		T-1 3/4	W2.1x4.9d Sub-Min Wedge	6	0.2	0.60	C-2R	0.80/20.3	0.23/5.9	1000
<b>84</b>	40968		T-1 3/4	W2.1x4.9d Sub-Min Wedge	6.3	0.04	0.03	C-2R	0.80/20.3	0.23/5.9	20000
<b>86</b>	40974		T-1 3/4	W2.1x4.9d Sub-Min Wedge	6.3	0.2	0.40	C-2F	0.80/20.3	0.23/5.9	20000
<b>86G</b>	00361		T-1 3/4	W2.1x4.9d Sub-Min Wedge	6.3	0.2	0.06	C-2F	0.80/20.3	0.23/5.9	20000
<b>18</b>	40350		T-1 3/4	W2.1x4.9d Sub-Min Wedge	14	0.04	0.13	C-2F	0.80/20.3	0.23/5.9	5000
<b>37</b>	40648		T-1 3/4	W2.1x4.9d Sub-Min Wedge	14	0.09	0.50	C-2F	0.80/20.3	0.23/5.9	2500
<b>74</b>	40928		T-1 3/4	W2.1x4.9d Sub-Min Wedge	14	0.1	0.70	C-2F	0.80/20.3	0.23/5.9	1000
<b>70</b>	40876		T-1 3/4	W2.1x4.9d Sub-Min Wedge	14	0.15	1.50	C-2F	0.80/20.3	0.23/5.9	100
<b>73</b>	40898		T-1 3/4	W2.1x4.9d Sub-Min Wedge	14	0.08	0.30	C-2F	0.80/20.3	0.23/5.9	15000
<b>85</b>	40972		T-1 3/4	W2.1x4.9d Sub-Min Wedge	28	0.04	0.30	C-2F	0.80/20.3	0.23/5.9	7000
<b>17</b>	44322		T-1 3/4	W2.1x4.9d Sub-Min Wedge	28	0.065	0.65	C-2F	0.80/20.3	0.23/5.9	5000

### T-1¾ BA-7S Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>SE1274</b>	40117		T-1 3/4	BA-7S	14.4	0.12	1.00	C-2F	0.80/20.3	0.23/5.9

### T-1¾ Midget Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	<b>1769</b>	40344		T-1 3/4	Midget Screw	2.5	0.2	0.20	C-2R	0.72/18.3	0.23/5.9
<b>1768</b>	40342		T-1 3/4	Midget Screw	6	0.2	0.60	C-2R	0.63/16.0	0.23/5.9	1000
<b>1775</b>	40346		T-1 3/4	Midget Screw	6.3	0.075	0.23	C-2R	0.63/16.0	0.23/5.9	1000
<b>378</b>	40662		T-1 3/4	Midget Screw	6.3	0.2	0.40	C-2F	0.72/18.3	0.23/5.9	20000
<b>8362</b>	42418		T-1 3/4	Midget Screw	14	0.08	0.30	C-2F	0.69/17.5	0.23/5.9	15000
<b>373</b>	40654		T-1 3/4	Midget Screw	14	0.08	0.50	C-2F	0.72/18.3	0.23/5.9	1500
<b>399</b>	40692		T-1 3/4	Midget Screw	28	0.04	0.30	C-2F	0.72/18.3	0.23/5.9	7000
<b>335</b>	40607		T-1 3/4	Midget Screw	28	0.04	0.34	C-2F	0.72/18.3	0.23/5.9	4000



23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679

www.eiko.com  
eiko@eiko.com

## MINIATURE

### T-1¾ Midget Flange Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	C7A	40029	T-1 3/4	Midget Flanged	105-125	0.7ma		Neon	0.94/23.9	0.23/5.9	25000	
	251	40524	T-1 3/4	Midget Flanged	2.47	0.3	0.45	C-2R	0.63/16.0	0.23/5.9	30	
	345	40624	T-1 3/4	Midget Flanged	6	0.04	0.03	C-2V	0.63/16.0	0.23/5.9	10000	
	A1H	40006	T-1 3/4	Midget Flanged	105-125	1.2ma		Neon	0.63/16	0.23/5.9	25000	
	C9A	40030	T-1 3/4	Midget Flanged	105-125	1.8ma		Neon	0.94/23.9	0.23/5.9	25000	
	328	40598	T-1 3/4	Midget Flanged	6	0.2	0.60	C-2R	0.63/16.0	0.23/5.9	1000	0.34CP at 5.0V
	380	40666	T-1 3/4	Midget Flanged	6.3	0.04	0.02	C-2V	0.63/16.0	0.23/5.9	20000	
	377	40660	T-1 3/4	Midget Flanged	6.3	0.075	0.23	C-2R	0.63/16.0	0.23/5.9	1000	
	381	40668	T-1 3/4	Midget Flanged	6.3	0.2	0.40	C-2F	0.63/16.0	0.23/5.9	20000	
	344	40622	T-1 3/4	Midget Flanged	10	0.014	0.002	C-2F	0.63/16.0	0.23/5.9	50000	
	394	40686	T-1 3/4	Midget Flanged	12	0.04	0.12	C-2F	0.63/16.0	0.23/5.9	20000	
	382	40670	T-1 3/4	Midget Flanged	14	0.08	0.30	C-2F	0.63/16.0	0.23/5.9	15000	
	330	40599	T-1 3/4	Midget Flanged	14	0.08	0.50	C-2F	0.63/16.0	0.23/5.9	1500	
	8918	41002	T-1 3/4	Midget Flanged	14	0.1	0.50	C-2F	0.63/16.0	0.23/5.9	10000	
	370	40650	T-1 3/4	Midget Flanged	18	0.04	0.15	C-2F	0.63/16.0	0.23/5.9	10000	
	385	40672	T-1 3/4	Midget Flanged	28	0.04	0.15	C-2F	0.63/16.0	0.23/5.9	10000	
	387	40678	T-1 3/4	Midget Flanged	28	0.04	0.30	C-2F	0.63/16.0	0.23/5.9	10000	
	327	40596	T-1 3/4	Midget Flanged	28	0.04	0.34	C-2F	0.63/16.0	0.23/5.9	4000	
	376	40658	T-1 3/4	Midget Flanged	28	0.06	0.34	C-2F	0.63/16.0	0.23/5.9	25000	
	367	49709	T-1 3/4	Midget Flanged	10	0.04	0.08	C-2F	0.63/16.0	0.23/5.9	5000	

### T-1¾ Midget Groove Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	379	40664	T-1 3/4	Midget Grooved	6.3	0.2	0.40	C-2F	0.63/16.0	0.23/5.9	20000
	337	40616	T-1 3/4	Midget Grooved	6.3	0.2	0.60	C-2R	0.63/16.0	0.23/5.9	1000
	386	40674	T-1 3/4	Midget Grooved	14	0.08	0.30	C-2F	0.63/16.0	0.23/5.9	40000
	388	40680	T-1 3/4	Midget Grooved	28	0.04	0.30	C-2F	0.63/16.0	0.23/5.9	25000
	334	40606	T-1 3/4	Midget Grooved	28	0.04	0.34	C-2F	0.63/16.0	0.23/5.9	4000

### T-1¾ Bi-Pin Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	7328	42400	T-1 3/4	Bi-Pin	6	0.2	0.60	C-2R	0.63/16.0	0.23/5.9	1000
	7362										
	7377	49056	T-1 3/4	Bi-Pin	6.3	0.075	0.23	C-2R	0.60/15.2	0.23/5.9	1000
	7381	40920	T-1 3/4	Bi-Pin	6.3	0.2	0.40	C-2F	0.63/16.0	0.23/5.9	20000
	7349	42408	T-1 3/4	Bi-Pin	6.3	0.2	0.55	C-2R	0.63/16.0	0.23/5.9	5000
	7371	40910	T-1 3/4	Bi-Pin	12	0.04	0.12	C-2F	0.63/16.0	0.23/5.9	10000
	7382	40922	T-1 3/4	Bi-Pin	14	0.08	0.30	C-2F	0.63/16.0	0.23/5.9	40000
	7330	40902	T-1 3/4	Bi-Pin	14	0.08	0.50	C-2F	0.63/16.0	0.23/5.9	1500
	7373	40912	T-1 3/4	Bi-Pin	14	0.1	0.50	C-2F	0.63/16.0	0.23/5.9	10000
	7374	49712	T-1 3/4	Bi-Pin	28	0.04	0.15	C-2F	0.60/15.2	0.23/5.9	10000
	7387	40926	T-1 3/4	Bi-Pin	28	0.04	0.30	C-2F	0.63/16.0	0.23/5.9	25000
	7327	40896	T-1 3/4	Bi-Pin	28	0.04	0.34	C-2F	0.60/15.2	0.23/5.9	4000
	7876	40954	T-1 3/4	Bi-Pin	28	0.06	0.34	C-2F	0.60/15.2	0.23/5.9	25000

### T-2 Candelabra Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	12RC	40223	T-2	Candelabra Screw	12	0.17	2000EFC	C-2F	1.22/31.0	0.91/23.1	12000	Reflector
	24RC	40515	T-2	Candelabra Screw	24	0.073	3000EFC	C-2F	1.22/31.0	0.91/23.1	10000	Reflector
	28RC	40549	T-2	Candelabra Screw	28	0.4	1500EFC	C-2F	1.22/31.0	0.91/23.1	5000	Reflector
	48RC	40743	T-2	Candelabra Screw	48	0.05	-	C-2F	1.22/31.0	0.91/23.1	10000	Reflector
	120RC	40253	T-2	Candelabra Screw	120	0.025	1000EFC	CC-7A	1.22/31.0	0.91/23.1	7500	Reflector
	120RC-Neon	40297	T-2	Candelabra Screw	120	3.5ma	n/a	Neon	1.22/31.0	0.91/23.1	10000	Reflector




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### T-2 Miniature Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	12RB	44016	T-2	Miniature Bayonet	12	0.17	2000EFC	C-2F	1.16/29.5	0.91/23.1	12000	Reflector
	60RB	40821	T-2	Miniature Bayonet	60	0.05	1800EFC	CC-7A	1.16/29.5	0.91/23.1	7500	Reflector
	120RB	40231	T-2	Miniature Bayonet	120	0.025	1000EFC	CC-7A	1.16/29.5	0.91/23.1	7500	Reflector


### T-2 Slide Base 5

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	6PSB5	40778	T-2	Slide Base 5	6	0.14	550EFC	C-2V	1.11/28.2	0.27/6.9	20000
	10ESB5	44014	T-2	Slide Base 5	10	0.035	450EFC	C-6	0.92/23.4	0.27/6.9	10000
	12ESB5	40218	T-2	Slide Base 5	12	0.04	650EFC	C-2V	0.92/23.4	0.27/6.9	7500
	12PSB5	40222	T-2	Slide Base 5	12	0.17	2000EFC	C-2F	1.11/28.2	0.27/6.9	12000
	16ESB5	40291	T-2	Slide Base 5	16	0.04	800EFC	C-2F	0.92/23.4	0.27/6.9	7500
	24CSB	40513	T-2	Slide Base 5	24	0.017	100EFC	C-2F	0.92/23.4	0.27/6.9	15000
	24ESB5	40507	T-2	Slide Base 5	24	0.04	850EFC	C-2F	0.92/23.4	0.27/6.9	8000
	24PSB5	40512	T-2	Slide Base 5	24	0.073	3000EFC	C-2F	1.11/28.2	0.27/6.9	10000
	28ESB5	40544	T-2	Slide Base 5	28	0.04	1500EFC	C-2F	0.92/23.4	0.27/6.9	6000
	28PSB5	40548	T-2	Slide Base 5	28	0.04	1600EFC	C-2F	1.11/28.2	0.27/6.9	5000
	48ESB5	40738	T-2	Slide Base 5	48	0.04	3000EFC	CC-2F	0.92/23.4	0.27/6.9	5000
	48PSB5	40742	T-2	Slide Base 5	48	0.05	1800EFC	C-7A	1.11/28.2	0.27/6.9	10000
	60PSB5	40822	T-2	Slide Base 5	60	0.05	2200EFC	CC-2F	1.11/28.2	0.27/6.9	7500
	120PSB5	40230	T-2	Slide Base 5	120	0.025	1200EFC	CC-7A	1.11/28.2	0.27/6.9	10000
	120PSB5-Neon	40229	T-2	Slide Base 5	120	3.5ma	n/a	Neon	1.12/28.5	0.27/6.9	10000
	155PSB5	40298	T-2	Slide Base 5	155	0.025	1200EFC	CC-7A	1.11/28.2	0.27/6.9	10000


### T-2 Slide Base 2

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	24E2	44018	T-2	Slide Base 2	24	0.035	600EFC	C-2F	1.69/42.9	0.27/6.9	7000	
	24EX	44020	T-2	Slide Base 2	24	0.035	600EFC	C-2F	1.69/42.9	0.27/6.9	8000	Rounded top, gray base, prick punch
	24X	40516	T-2	Slide Base 2	24	0.035	600EFC	C-2F	1.69/42.9	0.27/6.9	8000	gray base, prick punch
	48C2	49549	T-2	Slide Base 2	48	0.035	750EFC	C-2F	1.69/42.9	0.27/6.9	10,000	
	55C2	40765	T-2	Slide Base 2	55	0.05	1400EFC	C-2F	1.69/42.9	0.27/6.9	5000	


### T-2 Slide Base 3

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	24E3	40509	T-2	Slide Base 3	24	0.035	600EFC	C-2F	1.69/42.9	0.27/6.9	7000
	55C3	40768	T-2	Slide Base 3	55	0.05	1400EFC	CC-2F	1.69/42.9	0.27/6.9	5000

### T-2 Slide Base 6

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	52A	44324	T-2	Slide Base 6	24	0.03	430EFC	C-2F	0.92/23.4	0.27/6.9	8000

### T-2 SF6/6 Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life
	6609F	40838	T-2	SF6/6	12	0.05	0.20	C-8	1.26/32.0	0.24/6.1	5000
	6610F	40840	T-2	SF6/6	12	0.055	0.25	C-8	1.26/32.0	0.24/6.1	5000
	6612F	40841	T-2	SF6/6	12	0.25	1.00	C-8	1.26/32.0	0.24/6.1	5000
	6614F	40842	T-2	SF6/6	14	0.05	0.16	C-8	1.26/32.0	0.24/6.1	10000
	6615F	40844	T-2	SF6/6	14	0.08	0.30	C-8	1.26/32.0	0.24/6.1	10000




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### T-2 Wire Terminal Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Amps	Ext Res Reqd	Filament	MOL in/mm	MOD in/mm	Avg. Life	Replaces	Special Desc.
	<b>A1B</b>	40002	T-2	Wire Terminal	105-125	1/25	0.3ma	220K	Neon	0.50/12.7	0.25/6.4	25000		
<b>A1A</b>	40000	T-2	Wire Terminal	105-125	1/12	0.6ma	150K	Neon	1.00/25.4	0.25/6.4	25000		NE-2	
<b>A2A</b>	40008	T-2	Wire Terminal	105-125	1/15	0.7ma	100K	Neon	1.00/25.4	0.25/6.4	25000		NE-2A	
<b>A2B</b>	40010	T-2	Wire Terminal	105-125		0.7ma	100K	Neon	0.75/19.1	0.25/6.4	25000		NE-2V 2 inch leads	
<b>A9A</b>	40014	T-2	Wire Terminal	105-125	1/12	0.7ma	100K	Neon	1.00/25.4	0.25/6.4	25000		NE-2E 2 inch leads	
<b>A1C</b>	40004	T-2	Wire Terminal	105-125	1/7	1.2ma	47K	Neon	0.50/12.7	0.25/6.4	25000			
<b>A3C</b>	40012	T-2	Wire Terminal	105-125	1/4	1.8ma	30K	Neon	0.75/19.1	0.25/6.4	25000		NE-2U 2 inch leads	
<b>C2A</b>	40024	T-2	Wire Terminal	105-125	1/4	1.8ma	30K	Neon	1.00/25.4	0.25/6.4	25000		NE-2H	


### T-2¼ 2-Pin G-4 Base (Halogen)

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>787</b>	41402	T-2 1/4	2-Pin G-4		6	1.67	16	C-6	1.00/25.4	0.30/7.6	100
<b>788</b>	41404	T-2 1/4	2-Pin G-4		6	3.33	32	C-6	1.00/25.4	0.30/7.6	100	Halogen


### T-2¼ Printed Circuit Socket Base (Halogen)

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>882</b>	42100	T-2 1/4	PC Socket		12.8	0.35	3.8	C-6	1.18/30.0	0.72/18.3	2000
<b>2033</b>	40711	T-2 1/4	PC Socket		13.5	0.22	2.5	CC-6	1.18/30.0	0.72/18.3	2000	Halogen


### T-2¼ Sub-Miniature Wedge Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>1230X</b>	49003	T-2 1/4	Sub-Mini Wedge		14	0.214	2.10	C-2V	0.85/21.6	0.27/6.9	1000
<b>118F</b>	40685	T-2 1/4	Sub-Mini Wedge		14.4	0.124	0.07	C-2F	0.90/22.9	0.27/6.9	5000	Frosted

### T-2¼ Special Wedge Base (Halogen)

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>2040</b>	42470	T-2 1/4	Special Wedge		12.8	0.625	3.0	CC-6	1.29/32.8	0.38/9.6	500

### T-2½ Miniature Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>6MB</b>	40777	T-2 1/2	Miniature Bayonet		6	0.14	0.12	C-2V	1.19/30.2	0.33/8.4	20000
<b>12MB</b>	40220	T-2 1/2	Miniature Bayonet		12	0.17	0.35	C-2F	1.19/30.2	0.33/8.4	12000	
<b>24MB</b>	40510	T-2 1/2	Miniature Bayonet		24	0.073	0.50	C-2F	1.19/30.2	0.33/8.4	10000	
<b>28MB</b>	40546	T-2 1/2	Miniature Bayonet		28	0.04	0.29	C-2F	1.19/30.2	0.33/8.4	5000	
<b>48MB</b>	40740	T-2 1/2	Miniature Bayonet		48	0.05	0.50	C-2F	1.19/30.2	0.33/8.4	10000	
<b>60MB</b>	40820	T-2 1/2	Miniature Bayonet		60	0.05	0.73	CC-2F	1.19/30.2	0.33/8.4	7500	
<b>90MB</b>	40886	T-2 1/2	Miniature Bayonet		90	0.03	0.37	CC-7A	1.19/30.2	0.33/8.4	5000	
<b>120MB</b>	40226	T-2 1/2	Miniature Bayonet		120	0.025	0.36	CC-7A	1.19/30.2	0.33/8.4	10000	Substitute for 967 & 8-967
<b>120MB/6</b>	44022	T-2 1/2	Miniature Bayonet		120	0.052	1.43	CC-7A	1.19/30.2	0.33/8.4	3000	6 watt version
<b>130MB</b>	40249	T-2 1/2	Miniature Bayonet		130	0.025	0.36	CC-7A	1.19/30.2	0.33/8.4	10000	
<b>155MB</b>	40296	T-2 1/2	Miniature Bayonet		155	0.025	0.40	CC-7A	1.19/30.2	0.33/8.4	10000	




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### T-2½ 2-Pin G-4 Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		891	42116	T-2 1/2	2-Pin G-4	12.8	8	11.5	C-6	1.20/30.5	0.32/8.1	500


### T-2¾ Special Wedge Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		24	42240	T-2 3/4	Special Wedge	14	0.24	2.0	C-2V	0.91/23.1	0.34/8.7	1500
	24A	42244	T-2 3/4	Special Wedge	14	0.24	1.5	C-2V	0.91/23.1	0.34/8.7	1500	Painted Amber
	24NA	49670	T-2 3/4	Special Wedge	14	0.24	1.5	C-2V	0.91/23.1	0.34/8.7	1500	Hi-Temp Amber Paint


### T-2¾ 2-Pin G-4 Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		778	41400	T-2 3/4	2-Pin G-4	6	3.33	32	C-6	1.05/26.7	0.38/9.6	100
	789	41406	T-2 3/4	2-Pin G-4	12	1.17	22	C-6	1.05/26.7	0.38/9.6	200	Halogen


### T-2¾ Miniature Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		3893	40659	T-2 3/4	Miniature Bayonet	12	0.33	2.8	C-2R	1.09/27.7	0.38/9.6	300
	64111	40689	T-2 3/4	Miniature Bayonet	12	0.416	6.7	C-6	1.29/32.8	0.38/9.6	240	Halogen


### T-3 Miniature Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		1477	40282	T-3	Miniature Screw	24	0.17	3.3	C-2V	1.25/31.8	0.40/10.2	250

### T-3 Double End Cap Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		211-2	40480	T-3	Double End Cap	12.8	0.97	12.0	C-8	1.72/43.7	0.38/9.6	1000
	214-2	42040	T-3	Double End Cap	13.5	0.52	4.0	C-8	1.72/43.7	0.38/9.6	1000	
	212-2	42256	T-3	Double End Cap	13.5	0.74	6.0	C-8	1.72/43.7	0.38/9.6	2000	
	211-2B	42430	T-3	Double End Cap	12.8	0.37	-	C-8	1.72/43.7	0.43/11.0	1000	Painted Blue
	211-2R	42434	T-3	Double End Cap	12.8	0.37	-	C-8	1.72/43.7	0.43/11.0	1000	Painted Red

### T-3 Rigid Loop Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		561	40775	T-3	Rigid Loop	12.8	0.97	12.0	C-8	1.72/43.7	0.39/9.9	1000
	563	42058	T-3	Rigid Loop	13.5	0.52	4.0	C-8	1.72/43.7	0.39/9.9	1000	
	562	42052	T-3	Rigid Loop	13.5	0.74	6.0	C-8	1.72/43.7	0.39/9.9	2000	
	564	42070	T-3	Rigid Loop	14	0.44	2.0	C-8	1.72/43.7	0.39/9.9	2000	




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### T-3 HPR Base (Halogen)

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	Lumens	Filament	MOL in/mm	MOD in/mm	Avg. Life	Typ Use	Special Desc.
	<b>HPR52</b>	40052	T-3	SC Miniature Flanged (P13.5s)	2.8	0.85	35	C-6	1.25/31.8	0.38/9.6	10	2"D" Cells	Halogen
	<b>HPR53</b>	40058	T-3	SC Miniature Flanged (P13.5s)	4	0.85	48	C-6	1.25/31.8	0.38/9.6	25	3"D" Cells	Halogen
	<b>HPR44</b>	40034	T-3	SC Miniature Flanged (P13.5s)	4	1.0	54	C-6	1.25/31.8	0.38/9.6	300	3"NI CAD" Cells	Halogen
	<b>HPR55</b>	40070	T-3	SC Miniature Flanged (P13.5s)	5.2	0.5	48	C-6	1.25/31.8	0.38/9.6	15	4"C" Cells	Halogen
	<b>HPR50</b>	40040	T-3	SC Miniature Flanged (P13.5s)	5.2	0.85	85	C-6	1.25/31.8	0.38/9.6	25	4"D" Cells	Halogen
	<b>HPR36</b>	40031	T-3	SC Miniature Flanged (P13.5s)	5.5	1.0	93	C-6	1.25/31.8	0.38/9.6	40	4"D" Cells	Halogen
	<b>HPR40</b>	44000	T-3	SC Miniature Flanged (P13.5s)	6	0.67	75	C-6	1.25/31.8	0.38/9.6	50	6V Lantern	Halogen
	<b>HPR51</b>	40046	T-3	SC Miniature Flanged (P13.5s)	6.5	0.7	90	C-6	1.25/31.8	0.38/9.6	25	5"D" Cells	Halogen

### T-3 Miniature Bayonet Base (Neon)

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Amps	Ext Res Req'd	Fila-ment	MOL in/mm	MOD in/mm	Replaces	Avg Life
	<b>B1A</b>	40016	T-3	Miniature Bayonet	105-125	1/4	0.3ma	220K	Neon	1.19/30.2	0.38/9.6	NE51	25000
	<b>NE51-R</b>	40074	T-3	Miniature Bayonet	105-125	1/4	0.3ma	(220K Internal)	Neon	1.19/30.2	0.38/9.6		25000
	<b>B2A</b>	40018	T-3	Miniature Bayonet	105-125	1/4	1.2ma	47K	Neon	1.19/30.2	0.38/9.6	NE51H	25000
	<b>NE51H-R</b>	40076	T-3	Miniature Bayonet	105-125	1/4	1.2ma	(47K Internal)	Neon	1.19/30.2	0.38/9.6		25000
	<b>120MB-Neon</b>	40225	T-3	Miniature Bayonet	120		4.0ma	(18K Internal)	Neon	1.19/30.2	0.38/9.6		10000

### T-3¼ Miniature Wedge Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Fila-ment	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>159</b>	40303	T-3 1/4	Miniature Wedge	6.3	0.15	0.34	C-2R	1.06/26.9	0.40/10.2	5000	
	<b>259</b>	40534	T-3 1/4	Miniature Wedge	6.3	0.25	0.65	C-2R	1.06/26.9	0.40/10.2	5000	
	<b>555</b>	40783	T-3 1/4	Miniature Wedge	6.3	0.25	0.9	C-2R	1.06/26.9	0.40/10.2	3000	
	<b>555-B</b>	16043	T-3 1/4	Miniature Wedge	6.3	0.25	-	C-2R	1.06/26.9	0.40/10.2	3000	Painted Blue
	<b>555-G</b>	16044	T-3 1/4	Miniature Wedge	6.3	0.25	-	C-2R	1.06/26.9	0.40/10.2	3000	Painted Green
	<b>555-R</b>	16045	T-3 1/4	Miniature Wedge	6.3	0.25	-	C-2R	1.06/26.9	0.40/10.2	3000	Painted Red
	<b>555-Y</b>	16046	T-3 1/4	Miniature Wedge	6.3	0.25	-	C-2R	1.06/26.9	0.40/10.2	3000	Painted Yellow
	<b>147</b>	40278	T-3 1/4	Miniature Wedge	7	0.43	2.0	C-2R	1.06/26.9	0.40/10.2	1500	
	<b>2821</b>	42232	T-3 1/4	Miniature Wedge	12	0.25	1.76	C-2V	1.06/26.9	0.40/10.2	1000	ECE Type - W3W
	<b>1236X</b>	49013	T-3 1/4	Miniature Wedge	12	0.3	3.6	C-2V	1.06/26.9	0.40/10.2	20000	Xenon
	<b>2825</b>	40637	T-3 1/4	Miniature Wedge	12	0.4	4.0	C-2R	1.06/26.9	0.40/10.2	300	ECE Type - W5W
	<b>1210X</b>	49015	T-3 1/4	Miniature Wedge	12	0.833	10.0	C-2V	1.06/26.9	0.40/10.2	2000	Xenon
	<b>1211X</b>	49017	T-3 1/4	Miniature Wedge	12	0.917	10.0	C-2V	1.06/26.9	0.40/10.2	5000	Xenon
	<b>558</b>	40769	T-3 1/4	Miniature Wedge	13	0.33	-	C-2V	1.06/26.9	0.40/10.2	500	Lens End Bulb
	<b>192</b>	40424	T-3 1/4	Miniature Wedge	13	0.33	3.0	C-2V	1.06/26.9	0.40/10.2	1000	
	<b>1250X</b>	49019	T-3 1/4	Miniature Wedge	13.5	0.37	5.0	C-2V	1.06/26.9	0.40/10.2	500	Xenon
	<b>1250X-2</b>	49023	T-3 1/4	Miniature Wedge	13.5	0.37	4.0	C-2V	1.06/26.9	0.40/10.2	2000	Xenon
	<b>1250X-5</b>	49025	T-3 1/4	Miniature Wedge	13.5	0.37	3.0	C-2V	1.06/26.9	0.40/10.2	5000	Xenon
	<b>3652</b>	40655	T-3 1/4	Miniature Wedge	13.5	0.37	6.0	C-6	1.06/26.9	0.40/10.2	700	
	<b>658</b>	42272	T-3 1/4	Miniature Wedge	14	0.08	0.31	C-2F	1.06/26.9	0.40/10.2	15000	
	<b>161</b>	40304	T-3 1/4	Miniature Wedge	14	0.19	1.0	C-2F	1.06/26.9	0.40/10.2	4000	
	<b>158</b>	40300	T-3 1/4	Miniature Wedge	14	0.24	2.0	C-2V	1.06/26.9	0.40/10.2	500	
	<b>194</b>	40427	T-3 1/4	Miniature Wedge	14	0.27	2.0	C-2F	1.06/26.9	0.40/10.2	2500	
	<b>PC194</b>	00231	T-3 1/4	Printed Circuit Socket	14	0.27	2.0	C-2F	1.11/28.2	0.40/10.2	2500	
	<b>194LL</b>	42504	T-3 1/4	Miniature Wedge	14	0.27	2.0	C-2F	1.06/26.9	0.40/10.2	5000	Long Life
	<b>194A</b>	40430	T-3 1/4	Miniature Wedge	14	0.27	-	C-2F	1.06/26.9	0.40/10.2	2500	Painted Amber
	<b>194B</b>	42438	T-3 1/4	Miniature Wedge	14	0.27	-	C-2F	1.06/26.9	0.40/10.2	2500	Painted Blue
<b>194R</b>	42442	T-3 1/4	Miniature Wedge	14	0.27	-	C-2F	1.06/26.9	0.40/10.2	2500	Painted Red	
<b>194NA</b>	40432	T-3 1/4	Miniature Wedge	14	0.27	1.5	C-2F	1.06/26.9	0.40/10.2	2500	Hi-Temp Amber Paint	
<b>124</b>	40238	T-3 1/4	Miniature Wedge	14	0.27	1.5	C-2F	1.06/26.9	0.40/10.2	5000		
<b>1440X</b>	49029	T-3 1/4	Miniature Wedge	14	0.286	2.0	C-2V	1.06/26.9	0.40/10.2	4000	Xenon	
<b>193</b>	40426	T-3 1/4	Miniature Wedge	14	0.33	2.0	C-2F	1.06/26.9	0.40/10.2	15000		
<b>168</b>	40317	T-3 1/4	Miniature Wedge	14	0.35	3.0	C-2F	1.06/26.9	0.40/10.2	1500		
<b>PC168</b>	00229	T-3 1/4	Printed Circuit Socket	14	0.35	3.0	C-2F	1.11/28.2	0.40/10.2	1500		
<b>168LL</b>	42502	T-3 1/4	Miniature Wedge	14	0.35	3.0	C-2F	1.06/26.9	0.40/10.2	3000	Long Life	
<b>168NA</b>	00227	T-3 1/4	Miniature Wedge	14	0.35	2.0	C-2F	1.06/26.9	0.40/10.2	1500	Hi-Temp Amber Paint	

Continued on next page ►►



23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679

www.eiko.com  
eiko@eiko.com

## MINIATURE

### T-3¼ Miniature Wedge Base (Continued)

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Fila-ment	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>1450X</b>	49031		T-3 1/4	Miniature Wedge	14	0.357	2.0	C-2V	1.06/26.9	0.40/10.2	5000
<b>2841-BULK</b>			T-3 1/4	Miniature Wedge	24	0.125	1.76	C-2V	1.06/26.9	0.40/10.2	1000	ECE Type - W3W
<b>2450X</b>	50030		T-3 1/4	Miniature Wedge	24	0.208	4.4	C-2V	1.06/26.9	0.40/10.2	500	Xenon
<b>2470X</b>	50032		T-3 1/4	Miniature Wedge	24	0.3	4.4	C-2V	1.06/26.9	0.40/10.2	12000	Xenon
<b>2475X-1</b>	50036		T-3 1/4	Miniature Wedge	24	0.313	5.2	C-2V	1.06/26.9	0.40/10.2	10000	Xenon
<b>2410X-1</b>	50038		T-3 1/4	Miniature Wedge	24	0.417	7.2	C-2V	1.06/26.9	0.40/10.2	10000	Xenon
<b>585</b>	40759		T-3 1/4	Miniature Wedge	28	0.04	0.3	C-2F	1.06/26.9	0.40/10.2	7000	
<b>656</b>	40836		T-3 1/4	Miniature Wedge	28	0.06	0.62	C-2F	1.06/26.9	0.40/10.2	2500	
<b>657</b>	40837		T-3 1/4	Miniature Wedge	28	0.08	0.62	C-2F	1.06/26.9	0.40/10.2	15000	
<b>400</b>	40696		T-3 1/4	Miniature Wedge	28	0.1	1.6	C-2F	1.06/26.9	0.40/10.2	1000	
<b>464</b>	40728		T-3 1/4	Miniature Wedge	28	0.17	3.0	C-2F	1.06/26.9	0.40/10.2	1500	
<b>655</b>	49620		T-3 1/4	Miniature Wedge	28	0.20	3.0	C-2F	1.06/26.9	0.40/10.2	7000	
<b>2860X</b>	50042		T-3 1/4	Miniature Wedge	28	0.214	4.0	C-2V	1.06/26.9	0.40/10.2	1000	Xenon

### T-3¼ Miniature Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	<b>48</b>	40732		T-3 1/4	Miniature Screw	2	0.06	0.04	S-2	1.19/30.2	0.43/11.0
<b>41</b>	40700		T-3 1/4	Miniature Screw	2.5	0.5	0.50	C-2R	1.19/30.2	0.43/11.0	3000
<b>40</b>	40694		T-3 1/4	Miniature Screw	6.3	0.15	0.52	C-2R	1.19/30.2	0.43/11.0	3000
<b>46</b>	40726		T-3 1/4	Miniature Screw	6.3	0.25	0.90	C-2R	1.19/30.2	0.43/11.0	3000
<b>1487</b>	40284		T-3 1/4	Miniature Screw	14	0.2	1.40	C-2V	1.19/30.2	0.43/11.0	3000
<b>1821</b>	40370		T-3 1/4	Miniature Screw	28	0.17	3.4	C-2F	1.19/30.2	0.43/11.0	500

### T-3¼ Miniature Wedge Base with Wire Leads

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>193E-1</b>	42381		T-3 1/4	Miniature Wedge with Wire Leads	14	0.33	2.0	C-2F	1.06/26.9	0.40/10.2	15000

### T-3¼ Printed Circuit Socket

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>PC194</b>	00231		T-3 1/4	Printed Circuit Socket (B10d)	14	0.27	2.0	C-2F	1.11/28.2	0.40/10.2	2500

### T-3¼ Miniature Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	<b>49</b>	40744		T-3 1/4	Miniature Bayonet	2	0.06	0.04	C-6	1.19/30.2	0.43/11.0	1000
<b>43</b>	40706		T-3 1/4	Miniature Bayonet	2.5	0.5	0.5	C-2R	1.19/30.2	0.43/11.0	3000	
<b>1490</b>	40286		T-3 1/4	Miniature Bayonet	3.2	0.16	0.2	C-2R	1.19/30.2	0.43/11.0	3000	
<b>1804</b>	40352		T-3 1/4	Miniature Bayonet	4	0.06	0.07	C-2R	1.19/30.2	0.43/11.0	1000	
<b>1906</b>	40422		T-3 1/4	Miniature Bayonet	5	0.07	0.19	C-6	1.19/30.2	0.43/11.0	1000	
<b>1850</b>	40394		T-3 1/4	Miniature Bayonet	5	0.09	0.25	C-2R	1.19/30.2	0.43/11.0	1500	
<b>755</b>	40932		T-3 1/4	Miniature Bayonet	6.3	0.15	0.33	C-2R	1.19/30.2	0.43/11.0	20000	
<b>1847</b>	40390		T-3 1/4	Miniature Bayonet	6.3	0.15	0.38	C-2R	1.19/30.2	0.43/11.0	5000	
<b>47</b>	40730		T-3 1/4	Miniature Bayonet	6.3	0.15	0.5	C-2R	1.19/30.2	0.43/11.0	3000	
<b>47-B</b>	00025		T-3 1/4	Miniature Bayonet	6.3	0.15		C-2R	1.19/30.2	0.43/11.0	3000	
<b>47-G</b>	00026		T-3 1/4	Miniature Bayonet	6.3	0.15		C-2R	1.19/30.2	0.43/11.0	3000	
<b>47-R</b>	00027		T-3 1/4	Miniature Bayonet	6.3	0.15		C-2R	1.19/30.2	0.43/11.0	3000	
<b>47-Y</b>	00028		T-3 1/4	Miniature Bayonet	6.3	0.15		C-2R	1.19/30.2	0.43/11.0	3000	
<b>1866</b>	40400		T-3 1/4	Miniature Bayonet	6.3	0.25	0.65	C-2R	1.19/30.2	0.43/11.0	5000	

Continued on next page ►►



23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679

www.eiko.com  
eiko@eiko.com

## MINIATURE

### T-3¼ Miniature Bayonet Base (Continued)

Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
<b>44</b>	40716	T-3 1/4	Miniature Bayonet	6.3	0.25	0.9	C-2R	1.19/30.2	0.43/11.0	3000	
<b>1810</b>	40356	T-3 1/4	Miniature Bayonet	6.3	0.4	1.4	C-2R	1.19/30.2	0.43/11.0	3000	
<b>238</b>	49704	T-3 1/4	Miniature Bayonet	6.3	0.5	2.0	C-2R	1.19/30.2	0.43/11.0	2000	
<b>1888</b>	40406	T-3 1/4	Miniature Bayonet	7	0.5	2.0	C-2R	1.19/30.2	0.43/11.0	1500	
<b>1408</b>	40268	T-3 1/4	Miniature Bayonet	10	0.13	0.85	C-2V	1.19/30.2	0.43/11.0	250	
<b>1816</b>	40362	T-3 1/4	Miniature Bayonet	13	0.33	3.0	C-2V	1.19/30.2	0.43/11.0	1000	
<b>756</b>	40934	T-3 1/4	Miniature Bayonet	14	0.08	0.31	C-2F	1.19/30.2	0.43/11.0	15000	
<b>1815</b>	40360	T-3 1/4	Miniature Bayonet	14	0.2	1.4	C-2V	1.19/30.2	0.43/11.0	3000	
<b>1891</b>	40409	T-3 1/4	Miniature Bayonet	14	0.24	2.0	C-2F	1.19/30.2	0.43/11.0	500	
<b>256</b>	49813	T-3 1/4	Miniature Bayonet	14	0.27	1.6	C-2R	1.19/30.2	0.43/11.0	500	
<b>1893</b>	40413	T-3 1/4	Miniature Bayonet	14	0.33	2.0	C-2F	1.19/30.2	0.43/11.0	7500	
<b>1813</b>	40358	T-3 1/4	Miniature Bayonet	14.4	0.1	0.86	C-2V	1.19/30.2	0.43/11.0	1000	
<b>1892</b>	40412	T-3 1/4	Miniature Bayonet	14.4	0.12	0.75	C-2F	1.19/30.2	0.43/11.0	1000	
<b>1818</b>	40364	T-3 1/4	Miniature Bayonet	24	0.17	3.3	C-2V	1.19/30.2	0.43/11.0	250	
<b>1843</b>	40707	T-3 1/4	Miniature Bayonet	28	0.022	0.2	C-2F	1.19/30.2	0.43/11.0	3000	
<b>1819</b>	40366	T-3 1/4	Miniature Bayonet	28	0.04	0.34	C-2F	1.19/30.2	0.43/11.0	2500	
<b>1829</b>	40382	T-3 1/4	Miniature Bayonet	28	0.07	1.0	C-2F	1.19/30.2	0.43/11.0	1000	
<b>757</b>	40936	T-3 1/4	Miniature Bayonet	28	0.08	0.62	C-2F	1.19/30.2	0.40/10.2	15000	
<b>1820</b>	40368	T-3 1/4	Miniature Bayonet	28	0.1	1.6	C-2F	1.19/30.2	0.43/11.0	1000	
<b>1820BTS</b>	49790	T-3 1/4	Miniature Bayonet	28	0.1	1.6	C-2F	1.19/30.2	0.43/11.0	1000	Bulb is Butt Sealed
<b>1864</b>	40398	T-3 1/4	Miniature Bayonet	28	0.17	3.0	C-2F	1.19/30.2	0.43/11.0	1500	
<b>313</b>	40578	T-3 1/4	Miniature Bayonet	28	0.17	3.5	C-2F	1.19/30.2	0.43/11.0	500	
<b>1873</b>	40404	T-3 1/4	Miniature Bayonet	28	0.2	3.0	C-2F	1.19/30.2	0.43/11.0	7000	
<b>1822</b>	40372	T-3 1/4	Miniature Bayonet	36	0.1	2.1	C-2F	1.19/30.2	0.43/11.0	1000	
<b>1828</b>	40380	T-3 1/4	Miniature Bayonet	37.5	0.05	0.65	C-2F	1.19/30.2	0.43/11.0	3000	
<b>1835</b>	40386	T-3 1/4	Miniature Bayonet	55	0.05	1.1	C-2F	1.19/30.2	0.43/11.0	5000	
<b>8-3995</b>	44030	T-3 1/4	Miniature Bayonet	120	0.025	0.36	CC-7A	1.19/30.2	0.43/10.9	7500	
<b>967</b>	40386	T-3 1/4	Miniature Bayonet	120	0.025	0.36	CC-7A	1.19/30.2	0.43/11.0	7500	
<b>949</b>	49621	T-3 1/4	Miniature Bayonet	130	0.022	0.4	2C-2F	1.19/30.2	0.43/11.0	7000	
<b>1028.09.527-501</b>	49731	T-3 1/4	Miniature Bayonet	120	0.02	0.2	2C-2F	1.19/30.2	0.43/11.0		




### T-3¼ Rigid Loop Base (Xenon)

Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
<b>JF02XE</b>	50114	T-3 1/4	Rigid Loop	6	0.833	4.4	C-8	1.72/43.7	0.40/10.0	20000	Xenon
<b>JF03XE</b>	50118	T-3 1/4	Rigid Loop	12	0.417	4.8	C-8	1.72/43.7	0.40/10.0	3000	Xenon
<b>JF07XE</b>	50124	T-3 1/4	Rigid Loop	12	0.833	8.0	C-8	1.72/43.7	0.40/10.0	20000	Xenon
<b>JF08XE</b>	50126	T-3 1/4	Rigid Loop	12	1.0	12.0	C-8	1.72/43.7	0.40/10.0	3000	Xenon
<b>JF135050XE</b>	50096	T-3 1/4	Rigid Loop	13.5	0.37	4.0	C-8	1.72/43.7	0.40/10.0	15000	Xenon
<b>JF135100XE</b>	50098	T-3 1/4	Rigid Loop	13.5	0.74	9.55	C-8	1.72/43.7	0.40/10.0	15000	Xenon
<b>JF14XE</b>	50134	T-3 1/4	Rigid Loop	24	0.208	3.2	C-8	1.72/43.7	0.40/10.0	20000	Xenon
<b>JF14XE/F</b>	49639	T-3 1/4	Rigid Loop	24	0.208	3.2	C-8	1.72/43.7	0.40/10.0	20000	Xenon, Frosted
<b>JF13XE</b>	50132	T-3 1/4	Rigid Loop	24	0.208	4.4	C-8	1.72/43.7	0.40/10.0	3000	Xenon
<b>JF16XE</b>	50136	T-3 1/4	Rigid Loop	24	0.417	10.0	C-8	1.72/43.7	0.40/10.0	3000	Xenon
<b>JF17XE</b>	50138	T-3 1/4	Rigid Loop	24	0.417	7.2	C-8	1.72/43.7	0.40/10.0	20000	Xenon
<b>JF260050XE</b>	50100	T-3 1/4	Rigid Loop	26	0.192	4.0	C-8	1.72/43.7	0.40/10.0	15000	Xenon
<b>JF260100XE</b>	50102	T-3 1/4	Rigid Loop	26	0.385	9.55	C-8	1.72/43.7	0.40/10.0	15000	Xenon



### T-4 Single Contact Bayonet Base (Halogen)

Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
<b>796</b>	44023	T-4	SC Bayonet	12.8	35	60	C-6	2.50/63.5	0.48/12.2	300	Halogen
<b>795</b>	44019	T-4	SC Bayonet	12.8	50	108	C-6	2.50/63.5	0.48/12.2	200	Halogen
<b>795X</b>	44021	T-4	SC Bayonet	12.8	50	108	C-8	2.50/63.5	0.48/12.2	200	Halogen





23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679

www.eiko.com  
eiko@eiko.com

## MINIATURE

### T-4 Double Contact Index Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		H1157	44040	T-4	BAY15d	12.8/12.8	50/15	108/24	C-6/C-6	2.00/50.8	0.51/13.0	250/400

### T-4½ Single Contact Bayonet Base (Halogen)

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		H1156	44038	T-4 1/2	SC Bayonet	12.8	50	108	C-6	2.08/53	0.56/14.2	250

### T-4½ Miniature Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
		957	41040	T-4 1/2	Miniature Bayonet	9.84	0.5	4.6	C-2R	1.38/35.1	0.59/15.0
	1416	44340	T-4 1/2	Miniature Bayonet	12.8	0.8	8.0	C-2R	1.38/35.1	0.59/15.0	1000
	1414	49695	T-4 1/2	Miniature Bayonet	14	0.46	6.0	C-2R	1.38/35.0	0.59/15.0	500
	1495	40703	T-4 1/2	Miniature Bayonet	28	0.3	6.0	C-2F	1.38/35.1	0.59/15.0	500

### T-5 Single Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Fila-ment	MOL in/mm	MOD in/mm	Special Desc.	Avg Life
		1876	49699	T-5	SC Bayonet	3.5	2.5	6.5	C-6	1.75/44.5	0.65/16.5	
	1489	40407	T-5	SC Bayonet	6.5	2.75	24.0	C-6U	1.75/44.5	0.65/16.5	Filament parallel with bayonet pins	125
	5007	40647	T-5	SC Bayonet	12	0.42	4	C-2R	1.55/39.4	0.65/16.5	ECE Type - R5W	200
	5008	40663	T-5	SC Bayonet	12	0.83	10	C-2R	1.55/39.4	0.65/16.5	ECE Type - R10W	200

### T-5 Miniature Wedge Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
		909	41016	T-5	Miniature Wedge	6	0.62	3.0	C-2R	1.49/37.9	0.62/15.8	50
	914	41020	T-5	Miniature Wedge	4	0.9	3.5	C-2R	1.49/37.9	0.62/15.8	50	
	939	49683	T-5	Miniature Wedge	6	0.9	5	C-6	1.49/37.9	0.62/15.8	200	
	927	49682	T-5	Miniature Wedge	6	1.2	8	C-2R	1.49/37.9	0.62/15.8	50	
	908	41014	T-5	Miniature Wedge	6	1.5	12.0	C-2R	1.49/37.9	0.62/15.8	50	
	915	41021	T-5	Miniature Wedge	12	0.75	11.0	C-2R	1.49/37.9	0.62/15.8	50	
	901	42141	T-5	Miniature Wedge	12.8	0.31	2.9	C-2R	1.49/37.9	0.62/15.8	500	
	901A	43201	T-5	Miniature Wedge	12.8	0.31	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Amber
	901B	43204	T-5	Miniature Wedge	12.8	0.31	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Blue
	901G	43207	T-5	Miniature Wedge	12.8	0.31	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Green
	901R	43210	T-5	Miniature Wedge	12.8	0.31	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Red
	918	41025	T-5	Miniature Wedge	12.8	0.56	6.5	C-2R	1.49/37.9	0.62/15.8	500	
	918A	43302	T-5	Miniature Wedge	12.8	0.56	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Amber
	918B	43305	T-5	Miniature Wedge	12.8	0.56	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Blue
	918G	43308	T-5	Miniature Wedge	12.8	0.56	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Green
	918R	43311	T-5	Miniature Wedge	12.8	0.56	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Red
	923	41031	T-5	Miniature Wedge	12.8	0.91	12.5	C-2R	1.49/37.9	0.62/15.8	500	
	923G	43408	T-5	Miniature Wedge	12.8	0.91	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Green
	923R	43411	T-5	Miniature Wedge	12.8	0.91	-	C-2R	1.49/37.9	0.62/15.8	500	Painted Red
	912LL	42510	T-5	Miniature Wedge	12.8	1.0	12.0	C-2R	1.49/37.9	0.62/15.8	2000	Long Life
	922	41029	T-5	Miniature Wedge	12.8	0.98	15.0	C-2R	1.49/37.9	0.62/15.8	200	
	912	41017	T-5	Miniature Wedge	12.8	1.0	12.0	C-2R	1.49/37.9	0.62/15.8	1000	

Continued on next page ►►



23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679

www.eiko.com  
eiko@eiko.com

## MINIATURE

### T-5 Miniature Wedge Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	917	41024	T-5	Miniature Wedge	12.8	1.2	10.0	C-2F	1.49/37.9	0.62/15.8	1200	
	920	42157	T-5	Miniature Wedge	12.8	1.2	10.0	C-2F	1.49/37.9	0.62/15.8	1200	
	16120X	50044	T-5	Miniature Wedge	12.8	1.35	16	C-2R	1.53/38.9	0.62/15.8	10000	Xenon
	921	41026	T-5	Miniature Wedge	12.8	1.4	21.0	C-2R	1.49/37.9	0.62/15.8	1000	
	921LL	42512	T-5	Miniature Wedge	12.8	1.4	21.0	C-2R	1.49/37.9	0.62/15.8	2000	Long Life
	921X	50046	T-5	Miniature Wedge	12.8	1.4	21.0	C-2R	1.53/38.9	0.62/15.8	3000	Xenon
	921-FR	49562	T-5	Miniature Wedge	12.8	1.4		C-2R	1.49/37.9	0.62/15.8	1000	
	906	41012	T-5	Miniature Wedge	13	0.69	6.0	C-2F	1.49/37.9	0.62/15.8	1000	
	906B			Miniature Wedge								
	906G	00356	T-5	Miniature Wedge	13	0.69	-	C-2F	1.49/37.9	0.62/15.8	1000	Hi Temp Green Paint
	906R			Miniature Wedge								
	906Y	00359	T-5	Miniature Wedge	13	0.69	-	C-2F	1.49/37.9	0.62/15.8	1000	Hi Temp Yellow Paint
	916	41022	T-5	Miniature Wedge	13.5	0.54	2.0	C-2F	1.49/37.9	0.62/15.8	10000	
	916NA	42150	T-5	Miniature Wedge	13.5	0.54		C-2F	1.49/37.9	0.62/15.8	10000	Natural Amber
	904	41010	T-5	Miniature Wedge	13.5	0.69	4.0	C-2F	1.49/37.9	0.62/15.8	5000	5000+ hrs @ 14.0V
	1524X	50050	T-5	Miniature Wedge	24	0.3	5.4	C-2F	1.53/38.9	0.62/15.8	2500	Xenon
2410X-2	50054	T-5	Miniature Wedge	24	0.417	8.0	C-2F	1.53/38.9	0.62/15.8	3000	Xenon	
928	41032	T-5	Miniature Wedge	28	0.3	6.0	C-2F	1.49/37.9	0.62/15.8	500		

### T-6 Candelabra Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	15T6C-130V	43000	T-6	Candelabra Screw	130	15	90	C-7A	3.06/77.7	0.77/19.6	2000
	15T6C-145V	43002	T-6	Candelabra Screw	145	15	90	C-7A	3.06/77.7	0.77/19.6	2000
	25T6C-120V	43018	T-6	Candelabra Screw	120	25	190	C-7A	3.06/77.7	0.77/19.6	2000

### T-6 Single Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	3497	40645	T-6	SC Bayonet	12.8	2.1	45	C-6	2.00/50.8	0.79/20.1	600

### T-6 Double Contact Index Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	3496	40641	T-6	DC Index Bayonet	12.8/14	2.1/0.59	43/3	C-6/C-6	2.00/50.8	0.79/20.1	600 / 5000

### T-6 Wedge Double Filament Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	7440	40931	T-6	Wedge W3x16	13.5	1.85	37	C-6	1.75/44.5	0.79/20.1	300
	7443	40935	T-6	Wedge W3x16	13.5/13.5	1.85/0.44	35/2.78	C-6/C-6	1.75/44.5	0.79/20.1	500 / 1000




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### T-6½ Intermediate Screw Base (E17)

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Lumens	Fila-ment	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	20T6-1/2N-130V	43010	T-6 1/2	Intermediate Screw E17	130	20	180	C-8	5.5/139.7	0.83/21.1	3000	
	20T6-1/2F-130V	43012	T-6 1/2	Intermediate Screw E17	130	20	170	C-8	5.5/139.7	0.83/21.1	3000	Frosted
	20T6-1/2N-145V	44402	T-6 1/2	Intermediate Screw E17	145	20	170	C-8	5.5/139.7	0.83/21.1	3000	
	25T6-1/2N-130V	43020	T-6 1/2	Intermediate Screw E17	130	25	210	C-8	5.5/139.7	0.83/21.1	3000	
	25T6.5N/F-130V	43022	T-6 1/2	Intermediate Screw E17	130	25	200	C-8	5.5/139.7	0.83/21.1	3000	Frosted
	40T6-1/2N-130V	43038	T-6 1/2	Intermediate Screw E17	130	40	330	C-8	5.5/139.7	0.83/21.1	1500	
	40T6-1/2N/F-130V	43040	T-6 1/2	Intermediate Screw E17	130	40	320	C-8	5.5/139.7	0.83/21.1	1500	Frosted


### T-6½ Double Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Lumens	Fila-ment	MOL in/mm	MOD in/mm	Avg. Life	Special Desc.
	20T6-1/2DC-130V	43014	T-6 1/2	DC Bayonet	130	20	180	C-8	5.56/141.2	0.83/21.1	3000	
	20T6.5DC/F-130V	43016	T-6 1/2	DC Bayonet	130	20	170	C-8	5.56/141.2	0.83/21.1	3000	Frosted
	20T6-1/2DC-145V	44400	T-6 1/2	DC Bayonet	145	20	170	C-8	5.56/141.2	0.83/21.1	3000	
	25T6-1/2DC-130V	43024	T-6 1/2	DC Bayonet	130	25	210	C-8	5.5/139.7	0.83/21.1	3000	
	25T6.5DC/F-130V	43026	T-6 1/2	DC Bayonet	130	25	200	C-8	5.56/141.2	0.83/21.1	3000	Frosted


### T-7 Candelabra Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	15T7C-130V	43006	T-7	Candelabra Screw	130	15	90	C-7A	2.25/57.2	0.89/22.6	1500


### T-7 Intermediate Screw Base (E17)

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	15T7N-130V	43004	T-7	Intermediate Screw E17	130	15	90	C-7A	2.25/57.2	0.89/22.6	1500


### T-7 Double Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	15T7DC-130V	43008	T-7	DC Bayonet	130	15	90	C-7A	2.25/57.2	0.89/22.6	1500

### T-8 Candelabra Screw Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	25T8C-120V	43028	T-8	Candelabra Screw	120	25	180	C-7A	2.63/66.8	1.04/26.4	1500

### T-8 Intermediate Screw Base (E17)

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	25T8N-130V	43030	T-8	Intermediate Screw E17	130	25	180	C-7A	2.63/66.8	1.04/26.4	1500




23220 West 84<sup>th</sup> Street  
Shawnee, KS 66227

800.852.2217  
FAX 913.441.6679


www.eiko.com  
eiko@eiko.com

## MINIATURE


### T-8 Double Contact Bayonet Base

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	MSCP	Filament	MOL in/mm	MOD in/mm	Avg Life
	25T8DC-120V	49563	T-8	DC Bayonet	120	25	180	C-7A	2.63/66.8	1.04/26.4	1500
	25T8DC-130V	43032	T-8	DC Bayonet	130	25	180	C-7A	2.63/66.8	1.04/26.4	1500

### T-10 Medium Screw Base


	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Lumens	Filament	MOL in/mm	MOD in/mm	Avg Life	Special Desc.
	25T10-130V	43034	T-10	Medium Screw	130	25	210	C-8	5.19/131.8	1.25/31.8	1500	
	25T10/F-130V	43036	T-10	Medium Screw	130	25	200	C-8	5.19/131.8	1.25/31.8	1500	Frosted
	25T10/IF-120	41522	T-10	Medium Screw	120	25	-	C-8	5.19/131.8	1.25/31.8	1500	Inside Frosted
	40T10-130V	43042	T-10	Medium Screw	130	40	320	C-8	5.19/131.8	1.25/31.8	1500	
	40T10/F-130V	43044	T-10	Medium Screw	130	40	310	C-8	5.19/131.8	1.25/31.8	1500	Frosted

### TL-3 Miniature Screw Base


	Ordering Code	Bar Code	Bulb	Base	Volts	Amps	Lumens	Filament	MOL in/mm	MOD in/mm	Avg Life	Special Desc.
	112	40168	TL-3	Miniature Screw	1.2	0.25	S-2	0.93/23.6	0.38/9.6	5		1 "AA" Cell
	222	40492	TL-3	Miniature Screw	2.25	0.25	C-2R	0.93/23.6	0.38/9.6	5		2 "AA" Cells
	243	40520	TL-3	Miniature Screw	2.33	0.27	C-6	0.93/23.6	0.38/9.6	10		
	K222	40063	TL-3	Miniature Screw	2.33	0.6	C-2R	0.93/23.6	0.38/9.6	5	Krypton	

## AUTOMOTIVE

### HID Lamps - OE Replacement

	Ordering Code	Bar Code	Bulb	Base	Volts	Watts	Lumens	Filament	MOL in/mm	MOD in/mm	Avg Life	Special Desc.
	D1R			PK32 d3		35	2800				3000	For Reflector or Lens Optic Systems
	D1S			PK32 d2		35	3200				3000	For Projector Optic Systems
	D2R			P32 d-3		35	2800				2000	For Reflector or Lens Optic Systems
	D2S			P32 d-2		35	3200				2000	For Projector Optic Systems

### Halogen Forward Lighting

	Ordering Code	Bar Code	Volts	Watts	Bulb	Type	Base	Filament	Avg. Life	Special Desc.
	9003	42268	12.8/12.8	60/55	T-5	HB2	P43t-38	C-8/C-8	150/800	Halogen
	9003HW-SWTX	49111	12.8/12.8	90/82	T-5	HB2	P43t-38	C-8/C-8	150/800	Xenon, Up to 30% brighter than std halogen. Super White Coated Capsule
	9003SWTX	44128	12.8/12.8	60/55	T-5	HB2	P43t-38	C-8/C-8	150/800	Xenon, Up to 30% brighter than std halogen. Super White Coated Capsule
	9004	41008	12.8/12.8	65/45	T-4 3/4	HB1, Axial Prefocus	P29t	C-6/C-6	150/320	Halogen
	9004-Blue	43500	12.8/12.8	65/45	T-4 3/4	HB1, Axial Prefocus	P29t	C-6/C-6	150/320	Halogen
	9004HW	43504	12.8/12.8	100/80	T-4 3/4	HB1, Axial Prefocus	P29t	C-6/C-6	100/250	Halogen, High Watt
	9004HW-Blue	43524	12.8/12.8	100/80	T-4 3/4	HB1, Axial Prefocus	P29t	C-6/C-6	100/250	Halogen, High Watt
	9004HWSW	44031	12.8/12.8	100/80	T-4 3/4	HB1, Axial Prefocus	P29t	C-6/C-6	100/250	Halogen, High Watt, Super White Coated Capsule
	9004LL	41063	12.8/12.8	65/45	T-4 3/4	HB1, Axial Prefocus	P29t	C-6/C-6	250/850	Halogen, Long Life
	9004SW	44024	12.8/12.8	65/45	T-4 3/4	HB1, Axial Prefocus	P29t	C-6/C-6	150/320	Halogen, Super White Coated Capsule
	9004SWTX	44134	12.8/12.8	65/45	T-4 3/4	HB1, Axial Prefocus	P29t	C-6/C-6	150/320	Xenon, Up to 30% brighter than std halogen, Super White Coated Capsule
	9005	41052	12.8	65	T-3 1/4	HB3, Right-Angle Prefocus	p20d	C-8	150	Halogen
	9005-Blue	43508	12.8	65	T-3 1/4	HB3, Right-Angle Prefocus	p20d	C-8	150	Halogen
	9005HW	43544	12.8	100	T-3 1/4	HB3, Right-Angle Prefocus	p20d	C-8	100	Halogen, High Watt
	9005HWSW	44041	12.8	100	T-3 1/4	HB3, Right-Angle Prefocus	p20d	C-8	100	Halogen, High Watt, Super White Coated Capsule
	9005SW	44036	12.8	65	T-3 1/4	HB3, Right-Angle Prefocus	p20d	C-8	150	Halogen, Super White Coated Capsule

*Most Automotive Lamps are available boxed or in blister pack.*