




23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679

www.eiko.com
eiko@eiko.com


SEALED BEAM

PAR 36 Glass Sealed Beam



Ordering Code	Bar Code	Base	Volts	Watts	Approx Initial Max Beam CP	° Beam Spread Horiz x Vert	Filament	Avg. Life	MOL in/mm	MOD in/mm
4546	46072	Screw Terminals	4.7	0.5A	6300	3 x 3	C-2R	100	2.75/70	4 1/2 /114.3
4547	46074	Screw Terminals	4.75	1.25A	20,000	3 x 3	C-2R	100	2.75/70	4 1/2 /114.3
7613	46108	Screw Terminals	6	8	400	30 x 20	C-6	50	2.75/70	4 1/2 /114.3
4511	46060	Screw Terminals	6.2	30	2300	Trapezoidal	C-6	300	2.75/70	4 1/2 /114.3
4510	46058	Screw Terminals	6.4	25	800	80 x 20	C-6	300	2.75/70	4 1/2 /114.3
4515	46062	Screw Terminals	6.4	30	55,000	5 x 5	C-6	100	2.75/70	4 1/2 /114.3
4044	46008	Screw Terminals	12	12	1100	50 x 25	C-6	150	2.75/70	4 1/2 /114.3
4414	46028	Screw Terminals	12.8	18	1500	50 x 25	C-6	300	2.75/70	4 1/2 /114.3
4414A	46030	Screw Terminals	12.8	18	450	50 x 25	C-6	300	2.75/70	4 1/2 /114.3
4446	46048	Screw Terminals	12.8	25	400	80 x 80	C-6	300	2.75/70	4 1/2 /114.3
4416	46036	Screw Terminals	12.8	30	35,000	11 x 4	C-6	300	2.75/70	4 1/2 /114.3
4416R	46038	Screw Terminals	12.8	30	6000	11 x 4	C-6	300	2.75/70	4 1/2 /114.3
4405	46016	Screw Terminals	12.8	30	50000	5.5 x 5.5	C-6	100	2.75/70	4 1/2 /114.3
4406	46018	Screw Terminals	12.8	35	600	80 x 30	C-6	300	2.75/70	4 1/2 /114.3
4411	46020	Screw Terminals	12.8	35	2500	Trapezoidal	C-6	300	2.75/70	4 1/2 /114.3
4415	46032	Screw Terminals	12.8	35	9000	40 x 5	C-6	300	2.75/70	4 1/2 /114.3
4415A	46034	Screw Terminals	12.8	35	7000	40 x 5	C-6	300	2.75/70	4 1/2 /114.3
7400	46106	Slip-On Terminals	12.8	35	33,000	12 x 5	C-6	300	2.75/70	4 1/2 /114.3
4461	46050	Screw Terminals	12.8	60	6000	Trapezoidal	C-6	300	2.75/70	4 1/2 /114.3
4509	46057	Screw Terminals	13	100	110,000	12 x 6	C-6	25	2.75/70	4 1/2 /114.3
Q4632	46088	Screw Terminals	13	250	75,000	14 x 12	C-6	500	2.75/70	4 1/2 /114.3
4589	46084	Screw Terminals	28	50	5000	Trapezoidal	CC-6	400	2.75/70	4 1/2 /114.3
4502	46054	Screw Terminals	28	50	10,000	40 x 7	C-6	400	2.75/70	4 1/2 /114.3
4505	46056	Screw Terminals	28	50	45,000	11 x 5	CC-6	400	2.75/70	4 1/2 /114.3
4626	46086	Screw Terminals	28	150	25,000	40 x 9	CC-6	300	2.75/70	4 1/2 /114.3
4596	46085	Screw Terminals	28	250	150,000	11 x 12	CC-8	25	2.75/70	4 1/2 /114.3
4350	46014	Slip-On Terminals	36	60	2100	Trapezoidal	C-2V	400	2.75/70	4 1/2 /114.3
4340	46012	Slip-On Terminals	48	80	2500	Trapezoidal	C-2V	400	2.75/70	4 1/2 /114.3
36PAR36/ CAP/WFL32	81166	MP	12	36	1000	-	C-8	4000	2.36/50	4 1/2 /114.3

PAR 46 Glass Sealed Beam



Ordering Code	Bar Code	Base	Volts	Watts	Approx Initial Max Beam CP	° Beam Spread Horiz x Vert	Filament	Avg. Life	MOL in/mm	MOD in/mm
4531	46064	Screw Terminals	12.5	40	30,000	20 x 5	C-6	400	3.75/95	5 3/4 /146
4435	46044	Screw Terminals	12.8	30	75,000	5 x 5	C-6	100	3.75/95	5 3/4 /146
4413	46026	Screw Terminals	12.8	35	1100	80 x 20	C-6	300	3.75/95	5 3/4 /146
4419	46040	Screw Terminals	12.8	35	1600	Trapezoidal	C-6	300	3.75/95	5 3/4 /146
4412	46022	Screw Terminals	12.8	35	11,000	40 x 5	C-6	300	3.75/95	5 3/4 /146
4412A	46024	Screw Terminals	12.8	35	8800	40 x 5	C-6	300	3.75/95	5 3/4 /146
4436	46046	Screw Terminals	12.8	35	60,000	10 x 4	C-6	300	3.75/95	5 3/4 /146
H5006	46116	3 Contact Lugs	12.8/12.8	35/35	15,000/20,000	35 x 7/35 x 7	C-6/C-6	200/320	4.0/102	5 3/4 /146
4000	46000	3 Contact Lugs	12.8/12.8	37.5/60	11,000/25,000	34 x 7/34 x 7	C-6/C-6	200/320	4.0/102	5 3/4 /146
4040	46006	3 Contact Lugs	12.8/12.8	37.5/60	11,000/25,000	37 x 4/37 x 4	C-6/C-6	300/500	4.0/102	5 3/4 /146
5001	46096	2 Contact Lugs	12.8	50	35,000	26 x 5	C-6	200	4.0/102	5 3/4 /146
H5001	46114	2 Contact Lugs	12.8	50	55,000	26 x 5	C-6	200	4.0/102	5 3/4 /146
H7635	46122	Screw Terminals	12.8	50	160,000	6.5 x 4	C-6	100	3.75/95	5 3/4 /146
4478	46052	2 Contact Lugs	13	60	1600	56 x 32	2C-6	800	4.0/102	5 3/4 /146
4537	46066	Screw Terminals	13	100	200,000	11 x 6	C-6	25	3.13/80	5 3/4 /146
4007	46002	MP	13/13	100/100	50,000/20,000	5 x 6/7 x 13	C-6/C-6	25/25	4.0/102	5 3/4 /146
4049	46010	MP	13	150	300,000	15 x 7	C-6	15	3.13/80	5 3/4 /146
4578	46078	2 Contact Lugs	28	60	1600	55 x 30	2C-6	800	4.0/102	5 3/4 /146
4579	46080	3 Contact Lugs	28/28	80/60	24,000/11,000	25 x 25/7 x 7	CC-6/CC-6	400/400	4.0/102	5 3/4 /146
4570	46076	Screw Terminals	28	150	32,000	50 x 9	CC-6	300	3.75/95	5 3/4 /146
4581	46082	Screw Terminals	28	450	400,000	13 x 14	CC-8	10	3.13/80	5 3/4 /146




23220 West 84th Street
Shawnee, KS 66227

800.852.2217
FAX 913.441.6679


www.eiko.com
eiko@eiko.com

SEALED BEAM


PAR 56 Glass Sealed Beam

	Ordering Code	Bar Code	Base	Volts	Watts	Approx Initial Max Beam CP	° Beam Spread Horiz x Vert	Filament	Avg. Life	MOL in/mm	MOD in/mm
	4545	46070	Screw Terminals	12	100	225,000	9 x 5	C-6	100	4.5/114	0.28/7.0
	4543	46068	Screw Terminals	12.5	100	250,000	9 x 5	C-6	50	4.5/114	0.28/7.0
	6014	46098	3 Contact Lugs	12.8/12.8	60/50	32,000/25,000	34 x 7/34 x 7	C-6/C-6	200/320	5.0/127	0.28/7.0
	6015	46100	3 Contact Lugs	12.8/12.8	60/50	32,000/25,000	34 x 7/34 x 7	C-6/C-6	300/500	5.0/127	0.28/7.0
	H6024	46118	3 Contact Lugs	12.8/12.8	65/35	35,000/27,000	35 x 7/35 x 7	C-6/C-6	150/320	5.0/127	0.28/7.0


Rectangular 72mm x 140mm Glass Sealed Beam

	Ordering Code	Bar Code	Base	Volts	Watts	Approx Initial Max Beam CP	° Beam Spread Horiz x Vert	Filament	Avg. Life	MOL in/mm	Description
	H4351	46107	Right Angle, Plastic	12.8	55	SAE	SAE	C-8	500	4.0/102	Halogen Auto Headlamp, Lo Beam, Type K
	H4352	46109	Right Angle, Plastic	12.8	65	SAE	SAE	C-8	150	4.0/102	Halogen Auto Headlamp, Hi Beam, Type K


Rectangular 92mm x 150mm Glass Sealed Beam

	Ordering Code	Bar Code	Base	Volts	Watts	Approx Initial Max Beam CP	° Beam Spread Horiz x Vert	Filament	Avg. Life	MOL in/mm	Description
	H4703	46121	2 Contact Lugs	12.8	55	SAE	SAE	C-8	320	3.35/85	Halogen Auto Headlamp, Lo Beam, Type LF
	H4701	46119	2 Contact Lugs	12.8	65	SAE	SAE	C-8	150	3.35/85	Halogen Auto Headlamp, Hi Beam, Type UF

Rectangular 100mm x 165mm Glass Sealed Beam

	Ordering Code	Bar Code	Base	Volts	Watts	Approx Initial Max Beam CP	° Beam Spread Horiz x Vert	Filament	Avg. Life	MOL in/mm	Description
	H4656	46112	3 Contact Lugs	12.8/12.8	35/35	15,000/25,000	35 x 7/35 x 7	C-6/C-6	200/320	4.8/121	Halogen Auto Headlamp, Lo Beam, Type 2A1
	H4656HO/H6556	46113	3 Contact Lugs	12.8/12.8	40/55	SAE	SAE	C-8/C-8	200/700	4.8/121	Halogen Auto Headlamp, Hi Output, Hi/Lo Beam, Type 2A1
	4652	46092	3 Contact Lugs	12.8/12.8	40/60	12,500/22,500	34 x 7/34 x 7	C-6/C-6	200/320	4.8/121	Auto Headlamp, Low Beam, Type 2A1
	4651	46090	2 Contact Lugs	12.8	50	32,000	26 x 5	C-6	200	4.8/121	Auto Headlamp, Hi Beam, Type 1A1
	H4651	46110	2 Contact Lugs	12.8	50	55,000	26 x 5	C-6	200	4.8/121	Halogen Auto Headlamp, Hi Beam, Type 1A1
	H4666	46117	3 Contact Lugs	12.8/12.8	65/55	SAE	SAE	C-8/C-8	150/320	4.8/121	Halogen Auto Headlamp, Hi/Lo Beam, Type 2E1

Rectangular 142mm x 200mm Glass Sealed Beam

	Ordering Code	Bar Code	Base	Volts	Watts	Approx Initial Max Beam CP	° Beam Spread Horiz x Vert	Filament	Avg. Life	MOL in/mm	Description
	6052	46102	3 Contact Lugs	12.8/12.8	65/55	32,000/25,000	34 x 7/34 x 7	C-6/C-6	150/320	5.44/138	Auto Headlamp, Type 2B1
	H6054	46120	3 Contact Lugs	12.8/12.8	65/35	40,000/35,000	35 x 7/35 x 7	C-6/C-6	150/320	138 (5.44)	Auto Headlamp, Type 2B1
	H6054HO/H6554	46123	3 Contact Lugs	12.8/12.8	65/55	SAE	SAE	C-8/C-8	150/700	138 (5.44)	Halogen Auto Headlamp, Hi Output, Hi/Lo Beam, Type 2B1